

AG Ct13 (12++) Pro

Antifreeze Concentrate Ct13 Pro

N°: 921062

Description:

AG Ct13 (12++) Pro is a concentrated Monoethylene Glycol based coolant , in combination with the lobrid additive package (OAT-Si), intended for the protection of cooling systems of motor vehicles which must be diluted with water before use.

Especially recommended for cooling systems passenger cars and light duty vehicles when coolant meeting requirements of G12++(13) standard (VW TL 774 J) is required.

Application:

The Lobrid technology brings optimal protection for all engine metallic parts including aluminium and non-ferrous components. High performance additives protects against freezing, overheating, corrosion and scale.. Provides aluminium reinforced protection at high temperature. Eliminates the risk of scaling and deposits in the cooling system. Avoids cavitation and increases water pump lifetime. Compatible with gaskets, hoses, and plastic components. Can be mixed with ethylene glycol based coolants.

RECOMMENDATIONS:

Do not use pure product. Dilute with soft water according to the required freezing protection: see table. To maintain anti-corrosion properties, do not dilute below 33% of antifreeze. For optimal cooling effect, do not dilute above 66% of antifreeze. To be used for top-up or complete renewal of the cooling circuit for improved efficiency. Water for dilution: if possible use soft water (maximum hardness 35°F and chlorides and sulfates maximum contain 500 ppm). Drain intervals: Refer to the manufacturers' recommendation. Attention, control or drain the coolant only when the engine is cold. Can be mixed with ethylene glycol based coolants. This product should not be used to protect drinking water systems against freezing.

Instruction for use:

The cooling system should be completely emptied, flushed and filled with a mixture of distilled water and AG Ct13 (12++) Pro.

Volume Water Dilution		Solidification Point °C
AG Ct13 (12++) Pro	Water	
50%	50%	-38
66%	34%	-50
40%	60%	-23
33%	67%	-17

PRODUCT INFORMATION



Physical and Chemical Characteristics:

AG Ct13 (12++) Pro 100% Nitrite free, amine free, phosphate free, borate free.

Colour red or pink.

Specific Gravity, 20°C 1.12 typ.

Boiling Point 179°C typ.

Meets the requirements of the following standards and specification:

STN 66 8910, ASTM D 1384, MAN 324 Type SNF, Volvo VCS, MB 325.3, ,
Porsche/VW/Audi/Seat/Skoda VW - TL 774-G [G12++], VW - TL 774-J [G13] and also
MAN 324-SiOAT

Packages:

Different options are possible.