PRODUCT INFORMATION

Grease

DTO VHT02 EP2

Very High Temperature Grease EP 2

No: 9008

DTO VHT02 EP2 is a gray-black aluminum complex soap paste coated with special solids. It is walk-stable, thermally highly resilient and resistant to oxidation. In addition, good water resistance and good corrosion protection characterize the paste.

FIELDS OF APPLICATION
DTO VHT02 EP2 is a special paste for the lubrication of inserting and plug tools as well as wear bushings of hydraulic and pneumatic hammers.
Separating effect up to approx. +1100°C.
Do not use for the lubrication of roller and plain bearings!

DEUTSCHÖL RECOMMENDS THIS PRODUCT, WHEN THE FOLLOWING FILLING INSTRUCTIONS ARE REQUIRED:
KPF2U-20
NLGI 2

TYPICAL CHARACTERISTICS

Properties	Testing according	Data	Unit
Working temperature	DIN 51825	-20 to +1100	°C
Dropping Point	DIN ISO 2176	260	°C
Worked penetration (0,1 mm)	DIN ISO 2137	275	
Four-ball tester weld force	DIN 51350	6081	N
Copper corosion (24h/100°C)	DIN ISO 2160	1	
Base Oil Viscosity	DIN 51562	450	
Colour		gray-black	
Brief description	DIN 51502	MF2U-20	

01/2024