

PRODUCT INFORMATION

Grease



DTO MT04 EP2 (Blue)

Medium Temperature Grease EP 2

No: 9004

DTO MT04 EP2 is based on high quality basis oils with lithium soaps (Li-12-hydrosystearates) as thickening agents. This temperature-resistant wheel and roller bearing grease contains highly effective additives for improving the corrosion protection, ageing resistance as well as wear protection (EP-additives) and also adhesiveness..

FIELDS OF APPLICATION

DTO MT04 EP2 is appropriate for lubricating all types of rolling bearings in electric motors, machine tools, wheel hubs of passenger cars and commercial vehicles, etc.

DEUTSCHÖL RECOMMENDS THIS PRODUCT, WHEN THE FOLLOWING FILLING INSTRUCTIONS ARE REQUIRED:

KP2K-30

Mercedes Benz 267.0

MAN 283 Li-P2

NLGI 2

Central lubrication systems from e.g. BEKA-MAX, Delimon, Lincoln

TYPICAL CHARACTERISTICS

Properties	Testing according	Data	Unit
Working temperature	DIN 51825	-30 to +120	°C
Short time	DIN ISO 2176	up to +130	°C
Dropping Point	DIN ISO 2176	209	°C
Worked penetration (0,1 mm)	DIN ISO 2137	281	
Four-ball tester weld force	DIN 51350	2451	N
Copper corrosion (24h/100°C)	DIN ISO 2160	I	
Base Oil Viscosity	DIN 51562	130	
Colour		blue	
Brief description	DIN 51502	K2K-30	