PRODUCT INFORMATION

Grease

DTO MT03 EP2

Medium Temperature Grease EP 2

No: 9002

DTO MT03 EP2 is based on high quality basis oils with lithium soaps (Li-12-hydrosystearates) as thickening agents. It contains additives for improving the corrosion and rust protection. This lubricant is particularly oxidation and corrosion resistant.

FIELDS OF APPLICATION
DTO MT03 EP2 is suitable for lubricating of rolling and plain bearings and other lubricating points according to operation temperature range. The main application areas are greasing points of motor vehicles, devices, machines, conveyors as well as building machines etc.

DEUTSCHÖL RECOMMENDS THIS PRODUCT, WHEN THE FOLLOWING FILLING INSTRUCTIONS ARE REQUIRED:
KPF2U-30
NLGI 2

TYPICAL CHARACTERISTICS

Properties	Testing according	Data	Unit
Working temperature	DIN 51825	-30 to +120	°C
Short time	DIN ISO 2176	up to +130	°C
Dropping Point	DIN ISO 2176	204	°C
Worked penetration (0,1 mm)	DIN ISO 2137	283	
Four-ball tester weld force	DIN 51350	2452	N
Copper corosion (24h/100°C)	DIN ISO 2160	1	
Base Oil Viscosity	DIN 51562	130	
Colour		brown	
Brief description	DIN 51502	K2K-30	

01/2024