Product Information

Made in Germany

Article number: 5080751

Forstmeister

Special Chainsaw Oil Semi-Synthetic

DESCRIPTION

DEUTSCHÖL Forstmeister is a semi-synthetic, practice-proven chainsaw oils, suitable for use in motorised chain saws. Special combination o outstanding lubrication properties as well as excellent adhesiveness with good temperature behaviour. This chain saw oil is suitable for s operation. Excellent cooling effect guarantees low wear at optimum cutting speed.

THIS PRODUCT IS RECOMMENDED BY DEUTSCHÖL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

ISO VG 110, 150
Contains EP-additives (Extrem Pressure Antiwear)and special adhesion agent

TYPICAL CHARACTERISTICS

Properties	Testing according	110	150	Unit
Density 15°C	DIN 51757	0,870	0,888	g/ml
Pourpoint	DIN ISO 3016	< -25	< -20	°C
Viscosity 40 °C	DIN 51562	110	150	mm^2/sec
Viscosity 100 °C	DIN 51562	13,5	17	mm^2/sec
Flashpoint	DIN ISO 2592	225	235	°C
Brugger Test	DIN 51347-2	35	> 35	N/mm^2

Product Information

Made in Germany

Article number: 5080751

AVAILABLE PACKAGING

Item-Number						
VG 110	5080705-1	5080705-4	5080705-5	5080705-20	5080705-60	5080705-205
VG 150	5080751-1	5080751-4	5080751-5	5080751-20	5080751-60	5080751-205

The information in this product data sheet is based on years of experience of our team and our partners. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result, the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our team regarding the application conditions and requirements before the DEUTSCHÖL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.