Product Information

Made in Germany

Article number: 1081341

10W-40 UTTO AGRO EXTREM

CVT Tractors Hydrofluid

DESCRIPTION

DEUTSCHÖL 10W-40 UTTO AGRO EXTREM is a Tractor oil of the highest performance class with super multi-purpose properties for agricultural tractors and work machines. Can be used
as hydraulic oil and gear oil as well as wet brakes and clutches.

THIS PRODUCT IS RECOMMENDED BY DEUTSCHÖL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

SAE 10W-40
DIN 51524 HVLP, API GL-4, MIL-L-2105
VCE WB 102, VCE WB 101
AGCO POWERFLUID 821XL
Allison C-4
Caterpillar TO-2
CASE MS 1210
Case New Holland CNH MAT3540
Case New Holland CNH MAT3525
Case New Holland CNH MAT3509
Case New Holland CNH MAT3505
Fendt FNHA-2-C-200.00
Fendt FNHA-2-C-201.00
Ford ESN-M2C86-B
Ford ESN-M2C86-C
Ford ESN-M2C134-D
HCE-102, HCE-102W
John Deere JDM J20C
John Deere JDM J20D
Kubota UDT Fluid
Massey Ferguson CMS M1145
Massey Ferguson CMS M1143
Massey Ferguson CMS M1141
Massey Ferguson CMS M1135
Valtra G2-08
ZF TE-ML 03E 05F 06E, 06F 06K 17E, 21F

TYPICAL CHARACTERISTICS

Properties	Testing according	Data	Unit
Density at 15°C	DIN 51757	0,865	g/ml
CCS -25 °C	ASTM-D 5293	5100	cP
Pourpoint	DIN ISO 3016	< -30	°C
Viscosity at 40 °C	DIN 51562	92	mm²/sec
Viscosity at 100 °C	DIN 51562	14	mm²/sec
Viskosity Index	DIN ISO 2909	155	

Product Information

Made in Germany

Article number: 1081341

AVAILABLE PACKAGING



Item-number: 1081341-1 1081341-4 1081341-5 1081341-20



Item-number: 1081341-60 1081341-205

The information in this product data sheet is based on years of experience of our team and our partners. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result, the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our team regarding the application conditions and requirements before the DEUTSCHÖL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.