Product Information

Made in Germany

Article number: 1081040

10W-40 STOU Ultrafarm

10W-40 STOU

Super Tractor Universal Oil

DESCRIPTION

DEUTSCHÖL 10W-40 STOU Ultrafarm is specially formulated for use in agricultural tractors and various industrial machines. Designed for a uniform supply of diesel engines, manual transmissions, transfer cases, axle transmissions as well as hydraulic systems. It is also suitable for use in wet brakes and clutches.

THIS PRODUCT IS RECOMMENDED BY DEUTSCHÖL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

SAE 10W-40
API CG-4/CE/SF, API GL4,
ACEA E3, ACEA E7*²
DIN 51524 HVLP-D, MIL-L-2104 D
Allison C4, Caterpillar TO-2, Fendt Vario,
Case New Holland MAT 3525, 3526
Ford M2C 86 B, 134 D, 159 B/C
JI Case-MS 1204, 6, 7, 9, MAN 271
John Deere J 20 C, J 20 D, J 27 D
Massey Ferguson M1135, M 1139, M1143, M 1144, M 1145
Deutz DQC I-02
MB 228.1, MB 228.3 (nur Reinheitsniveau)
New Holland NH 024 C, 030 C
New Holland 410 B, 420 A
New Holland 820092101, 2, 3
Sauer Sundstrand/Danfoss Hydrostat, Sperry Vickers M 2950
Sperry Vickers / Eaton I-280-S
ZF TE-ML 05K, 06A*³, B*³, C*³, F, R*³, 7B
(*²soot control, piston cleanliness, bore polish, camshaft & cylinder wear)
(*³excluding latest demand from 100h KRL-Test)

TYPICAL CHARACTERISTICS

Properties	Testing according	Data	Unit
Density at 15°C	DIN 51757	0,865	g/ml
CCS -25 °C	ASTM-D 5293	5100	cP
Pourpoint	DIN ISO 3016	< -30	°C
Viscosity at 40 °C	DIN 51562	92	mm²/sec
Viscosity at 100 °C	DIN 51562	14	mm²/sec
Viskosity Index	DIN ISO 2909	155	
Base Number (TBN)	ASTM-D 2896	10,5	mgKOH/g

Product Information

Made in Germany

Article number: 1081040

AVAILABLE PACKAGING

Item-number:	 1081040-1	 1081040-4	 1081040-5	 1081040-20

Item-number:	 1081040-60	 1081040-205

The information in this product data sheet is based on years of experience of our team and our partners. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result, the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our team regarding the application conditions and requirements before the DEUTSCHÖL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.