Product Information

Made in Germany

Article number: 5180000

Forstprotect

BIO Chainsaw Oil "Blue Engel"

DESCRIPTION

DEUTSCHÖL Forstprotect with „Blue Angel" approval, practice-proven chainsaw oil, based on renewable natural resource rape oil, provides high viscosity of ISO VG 100. Special additives protects the product against premature ageing, resin deposits and improves adhesive and sliding properties. Forstprotect is suitable for reliable lubrication of faster engine and electric saw units, used for all types of wood. An optimum lubrication is guaranteed, also at low operation temperatures.

The product may not be mixed with synthesis or mineral oil.

DEUTSCHÖL BIO-Saw Chain Oil Forstprotect complies with the Ecolabel criteria „Blauer Engel" (RAL-UZ 178), as the share of renewable natural resource according to DIN CEN/TS 16137 (DIN SPEC 91236) ca. 95%.

Forstprotect can be stored for at least 4 years.

TYPICAL CHARACTERISTICS

Properties	Testing according	Data	Unit
Density at 15°C	DIN 51757	0,922	g/ml
Flashpoint	DIN ISO 2592	230	°C
Viscosity at 40 °C	DIN 51562	100	mm²/sec
Colour	green		

Product Information

Made in Germany

Article number: 5180000

AVAILABLE PACKAGING

Item-number:	 5180000-1	 5180000-4	 5180000-5	 5180000-20

Item-number:	 5180000-60	 5180000-205

The information in this product data sheet is based on years of experience of our team and our partners. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result, the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our team regarding the application conditions and requirements before the DEUTSCHÖL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.