Product Information

Made in Germany

Article number: 8031200

Topas 2

Multipurpose Grease

BESCHREIBUNG

DEUTSCHÖL Topas 2 is based on high quality basis oils with lithium soaps (Li-12-hydrosystearates) as thickening agents. It contains additives for improving the corrosion and rust protection. This lubricant is particularly oxidation and corrosion resistant.

FIELDS OF APPLICATION

DEUTSCHÖL Topas 2 is suitable for lubricating of rolling and plain bearings and other lubricating points according to operation temperature range. The main application areas are greasing points of motor vehicles, devices, machines, conveyors as well as building machines etc.

DEUTSCHÖL RECOMMENDS THIS PRODUCT, WHEN THE FOLLOWING FILLING INSTRCTIONS ARE REQUIRED:

KP2K-30 KP2K-30

TYPICAL CHARACTERISTICS

Properties	Testing according	Data	Unit
Working temperature	DIN 51825	-30 to +120	°C
Short time		up to +130	°C
Dropping Point	DIN ISO 2176	204	°C
Worked penetration (0,1 mm)	DIN ISO 2137	283	
Four-ball tester weld force	DIN 51350	2452	N
Copper corosion (24h/100°C)	DIN ISO 2160	1	
Base Oil Viscosity	DIN 51562	130	mm^2/s
Colour		brown	
Brief description	DIN 51502	K2K-30	

Product Information

Made in Germany

Article number: 8031200

AVAILABLE PACKAGING

				
Item-Number	8031200-400	8031200-400LS	8031200-500	8031200-1
				
Item-Number	8031200-5	8031200-15	8031200-25	8031200-50

The information in this product data sheet is based on years of experience of our team and our partners. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result, the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our team regarding the application conditions and requirements before the DEUTSCHÖL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.