Product Information

Article number: 1090040

40 Diesel Oil

Motor Oil for Trucks and Commercial Vehicles

DESCRIPTION

DEUTSCHÖL 40 Diesel Oil is a high-quality diesel motor oil, suitable for all-year use in all heavily loaded naturally aspirated and turbo diesel engines. Selected additives guarantee high engine cleanliness with high wear protection. Suited for fuels with more than 0.5 wt.-% sulphur content. When using high-sulphur fuels, the oil change intervals should be reduced.

THIS PRODUCT IS RECOMMENDED BY DEUTSCHÖL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

SAE 40
API CF-4, SJ
MB 227.0, MB 228.0
Allison C-3
Cat TO-2
MAN 271
Volvo VDS
MTU Level1
MIL-L-2104 D, 46152 B

TYPICAL CHARACTERISTICS

Properties	Testing according	Data	Unit
Density at 15°C	DIN 51757	0,89	g/ml
Pourpoint	DIN ISO 3016	< -10	°C
Viscosity at 40 °C	DIN 51562	145	mm²/sec
Viscosity at 100 °C	DIN 51562	15	mm²/sec
Viskosity Index	DIN ISO 2909	104	
Base Number (TBN)	ASTM-D 2896	10	mgKOH/g

Product Information

Made in Germany

Article number: 1090040

Available Packaging



Item-number: 1090040-1 1090040-4 1090040-5 1090040-20



Item-number: 1090040-60 1090040-205

The information in this product data sheet is based on years of experience of our team and our partners. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result, the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our team regarding the application conditions and requirements before the DEUTSCHÖL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning.
Please note: Our products may not be used in aircraft and spacecraft or parts thereof.