Product Information

Made in Germany

Article number: 1000002

2T Profi

2T Motor Oil Combisynt

DESCRIPTION

DEUTSCHÖL 2T Profi contains petrol stabiliser and is based on a high proportion of fully synthetic components. Formulated for air and water-cooled high-performance two-stroke engines. Highly effective against wear. Guarantees excellent high temperature stability properties. Suitable for mixed and separate lubrication systems.

THIS PRODUCT IS RECOMMENDED BY DEUTSCHÖL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

SAE 30
API TC
Global GD
ISO EGD
JASO FD
T.I.S.I
Honda DIO AF27
Husqvarna 242
Kawasaki KH125M
Suzuki SX800R
Yamaha CE50S
Yamaha RD350B

ADVANTAGES

- No segregation
- Smoke-free combustion
- Oxidation stable
- High wear protection
- Excellent corrosion protection

TYPICAL CHARACTERISTICS

Properties	Testing according	Data	Unit
Density at 15°C	DIN 51757	0,860	g/ml
Flashpoint	DIN ISO 2592	175	°C
Pourpoint	DIN ISO 3016	< -40	°c
Viscosity at 40 °C	DIN 51562	59	mm²/sec
Viscosity at 100 °C	DIN 51562	10	mm²/sec

Product Information


Made in Germany

Article number: 1000002

AVAILABLE PACKAGING



Item-number.	1000002-1	1000002-4	1000002-5	1000002-20



Item-number:	1000002-60	1000002-205

The information in this product data sheet is based on years of experience of our team and our partners. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result, the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our team regarding the application conditions and requirements before the DEUTSCHÖL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.