Product Information

Made in Germany

Article number: 1098540

8005 HP Power Generator

High Performance Gas Motor Oil Low Ash

DESCRIPTION

DEUTSCHÖL 8005 HP Power Generator represents the highest performance class of gas engine oils. It consists of synthetic basic components and provides a high level of protection against deposits and wear. The excellent protection against oxidation and the long-lasting additives guarantee the longest oil change intervals. Furthermore, the low-ash formulation protects catalysts.

THIS PRODUCT IS RECOMMENDED BY DEUTSCHÖL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

SAE 40
Caterpillar MWM TR 0199-99-2105/7
Wartsila 34SG, Wartsila 32DF
Wartsila 28SG, Wartsila 220 SG
GE Waukesha (Kraft-Wärme-Kopplung)
MAN D365600-1.35-1
MAN D6628 3.3.6-01

TYPICAL CHARACTERISTICS

Properties	Testing according	Data	Unit
Density at 15°C	DIN 51757	0,858	g/ml
Pourpoint	DIN ISO 3016	< -20	°C
Viscosity at 40 °C	DIN 51562	120	mm²/sec
Viscosity at 100 °C	DIN 51562	13,5	mm²/sec
Viskosity Index	DIN ISO 2909	109	
Base Number (TBN)	ASTM-D 2896	5,7	mgKOH/g
Sulphated ash	ASTM D 874	0,49	%

Product Information

Made in Germany

Article number: 1098540

AVAILABLE PACKAGING

Item-number:	 1098540-1	 1098540-4	 1098540-5	 1098540-20

Item-number:	 1098540-60	 1098540-205

The information in this product data sheet is based on years of experience of our team and our partners. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result, the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our team regarding the application conditions and requirements before the DEUTSCHÖL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.