Product Information

Made in Germany

Article number: 1060535

5W-30 DPF VW Plus 5W-30 LL III uni DPF

Motor Oil for Petrol and Diesel Engines

DESCRIPTION

DEUTSCHÖL 5W-30 DPF VW Plus is a Low SAPS, low-friction motor oil based on advanced HC synthesis technology. Specially formulated for the requirements of modern petrol and diesel engines from VW/Audi, Mercedes and BMW. The low content of ash-forming substances (low SAPS) ensure an optimum functionality in catalysts and diesel particulate filters at the longest oil change intervals

THIS PRODUCT IS RECOMMENDED BY DEUTSCHÖL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

SAE 5W-30
ACEA C2/C3
BMW Longlife 04
Fiat 9.55535-S3
Ford M2C917-A
MB 229.51
Porsche C30
VW 504.00, 507.00
VW 502.00, 505.00, 505.01, 503.00, 503.01

ADVANTAGES

- excellent wear protection
- outstanding oxidation- and temperature stability
- low friction losses
- optimum engine cleanliness due to excellent cleaning properties
- long oil changing intervals
- improved fuel efficiency

TYPICAL CHARACTERISTICS

Properties	Testing according	Data	Unit
Density at 15°C	DIN 51757	0,855	g/ml
CCS -30 °C	ASTM-D 5293	5800	cP
Pourpoint	DIN ISO 3016	< -35	°C
Viscosity at 40 °C	DIN 51562	70	mm²/sec
Viscosity at 100 °C	DIN 51562	11,8	mm²/sec
Viskosity Index	DIN ISO 2909	165	

Product Information

Made in Germany

Article number: 1060535

AVAILABLE PACKAGING



Item-number:.	1060535-1	1060535-4	1060535-5	1060535-20



Item-number:	1060535-60	1060535-205

The information in this product data sheet is based on years of experience of our team and our partners. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result, the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our team regarding the application conditions and requirements before the DEUTSCHÖL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning.
Please note: Our products may not be used in aircraft and spacecraft or parts thereof.