Product Information

Made in Germany

Article number: 1060022

0W-20 DPF-2 Ultra 0W-20 C2 DPF

Combisynt Motor Oil for Petrol and Diesel Engines

DESCRIPTION

DEUTSCHÖL 0W-20 DPF-2 Ultra contents fully synthetic and HC synthetic oils with selected additives provide improved wear protection, fuel economy and low oil consumption. Suitable for gasoline and diesel engines with special exhaust aftertreatment systems (e.g. DPF).

THIS PRODUCT IS RECOMMENDED BY DEUTSCHÖL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

SAE 0W-20
API SN/RC
ACEA C2
ILSAC GF-5
Fiat 9.55535-DSX
PSA B71 2312
Volvo VCC RBS0-2AE

ADVANTAGES

- excellent wear protection
- outstanding oxidation- and temperature stability
- low friction losses
- optimum engine cleanliness due to excellent cleaning properties
- long oil changing intervals
- improved fuel efficiency

TYPICAL CHARACTERISTICS

Properties	Testing according	Data	Unit
Density at 15°C	DIN 51757	0,849	g/ml
CCS -35 °C	ASTM-D 5293	5200	cP
Pourpoint	DIN ISO 3016	< -40	°C
Viscosity at 40 °C	DIN 51562	47	mm²/sec
Viscosity at 100 °C	DIN 51562	8,7	mm²/sec
Viskosity Index	DIN ISO 2909	160	

Product Information

Made in Germany

Article number: 1060022

AVAILABLE PACKAGING

				
Item-number:.	1060022-1	1060022-4	1060022-5	1060022-20

		
Item-number:	1060022-60	1060022-205

The information in this product data sheet is based on years of experience of our team and our partners. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result, the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our team regarding the application conditions and requirements before the DEUTSCHÖL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning.
Please note: Our products may not be used in aircraft and spacecraft or parts thereof.