



POLE & WALL MOUNT

Remote Security Agent Pole/ Wall Mount

HW-RSA-13AD-W

Compute

System Memory	8 GB
Storage	2 TB NVMe, up to 30 days storage

Cameras & Speaker (Uniview)

PTZ (one)	Model: IPC6424SR-X25-VF-B Resolution: 4MP (2688 × 1520) Sensor: 1/2.8" CMOS FOV: H: 52.2°, V: 30.8° Zoom: 25x (optical), 16x (digital)
Bullet (two)	Model: IPC2314SR-ADF28KM-WP Resolution: 4MP (2688 × 1520) Sensor: 1/1.8" CMOS FOV: H: 110.4°, V: 60.5°
Speaker (one)	Model: IPS302030-S Power: 30W Two-Way Audio: Supported

System Environmental

Operating Temperature	-15°C ~ 60°C (5°F ~ 140°F), IEC60068-2 @ 0.5 m/s airflow
Storage Temperature	-40°C ~ 85°C (-40°F ~ 185°F)
Storage Humidity	5% ~ 95% @ 40°C, non-condensing
Anti-Vibration	3.5 Grm / 5~500 Hz / operation
Anti-Shock	50G peak acceleration
Certification	CE / FCC Class A
Enclosure Ingress Protection	IP56

System Power (Combined)

AC Power Input	110–277V AC, 8A (2.2 kW max capacity)
Power Control Module	360W built-in PCM — regulates & distributes system load
DC Power Outputs	48V DC: 3A max (up to 150W) 12V DC: 5A max (up to 60W) 12V DC: 2x fan ports, 1A max each 12V DC: 1x LED port, 1A max

Mechanical

MSP-AC-00 Enclosure	18.92"L x 13.35"W x 23.45"H (incl. mount) Weight: 49.3 lb
Mounting	Pole or wall install; 'French Cleat' hanging mount w/ set screws (all hardware included for both mount types)

Communication & Connectivity

PoE Switch	8-port PoE+
Router (optional)	Peplink MAX-BR1-MINI-5GN-T-M-PRM (not incl. in MSRP)
Data Plan (optional)	Unlimited data plan with one of the major carriers (not incl. in MSRP)

Enclosure Protection & Installation

- Integrated Protection: built-in air circuit breaker for electrical fault protection.
- Thermal Management: dual (2) integrated cooling fans, managed by the 360W PCM.
- AC Power Input Cable: 70cm cable, IP68 waterproof stainless-steel connector, UL-rated quick-connects.
- Cable Management & Port Access: NPT 3/4" knockout with protective cap.
- Expansion: dedicated mounting points for 4G/5G antennas and a horn speaker.