

## 120W UNDER CANOPY LIGHT



Designed to penetrate **Beneath Dense Canopies** 











**SPECTRUM** 





312 µmol/s

2.6 µmol/j\* \*(±5%)



\*2 LIGHT FIXTURES PER BOX







Model: WUC120

## **UNDER CANOPY LIGHT** | 120W

The Wachsen Pro Under Canopy Light is engineered for durability, longevity, and efficiency in demanding indoor grow environments. With a waterproof IP65 rating and a wide 120° upward beam angle, it's built to thrive under dense plant canopies, delivering consistent performance and optimal coverage. This under-canopy LED spectrum is optimized with a strong peak in deep red (660 nm) and a secondary blue peak (~450 nm) to drive photosynthesis in shaded lower leaves. The targeted output enhances light penetration, promoting uniform growth and maximizing yield. Minimal green and far-red output ensures efficient energy use where plants need it most.



## **TECHNICAL SPECIFICATIONS**

## WACHSEN PRO - UNDER CANOPY LIGHT - LED FIXTURE

Power Consumption	120W	
Input Voltage	AC120-277V 50/60Hz	
Efficacy (PPE)	2.6 µmol/j (±5%)	
PPF Output	312 µmol/s	
Dimming Control	0-10V	
Network Port	RJ12	
Power Factor	>0.95	
Thermal Management	Passive Cooling	
Waterproof Rating	IP65	
Operational Temp.	14°F ~ 104 °F (-10 °C ~ +40 °C)	
LED Lifespan (Estimated)	Q90 > 36,000 hrs	
Dimensions	46.8" x 1.6" x 2.2"	
Weight LED Lamp	15.1 lb.	





Ultra Wide-Beam Emission Angle

Optional Adjustable Stands\* (Height Range: 8" to 15") \*Stands Sold Separately



Input		Linkable
120-277VAC	120V	7 PCS
	230V	13 PCS
	240V	14 PCS
	277V	16 PCS







UNDER CANOPY LIGHT | 120W













