

Load Attachment Products

Lifting Point working load application factors



										
Number of legs	1	2	1	2	2	2	2	3-4	3-4	3-4
Load Direction	0°	0°	90°	90°	0-45°	45-60°	unsymm	0-45°	45-60°	unsymm

Part Code	Thread	WLL tonnes									
		1	2	1	2	1	2	1	2	1	2
8-211-003	M8	0.3	0.6	0.3	0.6	0.42	0.3	0.3	0.63	0.45	0.3
8-211-006	M10	0.63	1.26	0.63	1.26	0.88	0.63	0.63	1.32	0.95	0.63
8-211-010	M12	1	2	1	2	1.4	1	1	2.1	1.5	1
8-211-012	M14	1.2	2.4	1.2	2.4	1.7	1.2	1.2	2.5	1.8	1.2
8-211-015	M16	1.5	3.1	1.5	3	2.1	1.5	1.5	3.1	2.2	1.5
8-211-020	M18	2	4	2	4	2.8	2	2	4.2	3	2
8-211-025	M20	2.5	5	2.5	5	3.5	2.5	2.5	5.2	3.7	2.5
8-211-040	M24	4	8	4	8	5.6	4	4	8.4	6	4
8-211-042	M27	4	8	4	8	5.6	4	4	8.4	6	4
8-211-050	M30	5	10	5	10	7	5	5	10.5	7.5	5
8-211-070	M36	7	14	7	14	9.8	7	7	14.7	10.5	7
8-211-080	M36	8	16	8	16	11.2	8	8	16.8	12	8
8-211-100	M42	10	20	10	20	14	10	10	21	15	10
8-211-150	M42	15	30	15	30	21	15	15	31.5	22.5	15
8-211-200	M48	20	40	20	40	28	20	20	42	30	20