


Load Attachment Products

Lifting Point metric thread

- Rotates through 360° and pivots 90°.
- Manufactured from alloy steel, quenched and tempered.
- Manufactured and tested in accordance with EN1677-1.
- Certified by DGUV GS-OA 15-04.
- Load rated parts are 100% magnaflux crack detected.
- Individual forged parts and cap screw are traceable to Test Certification.
- Bolts are Metric thread (ASME / ANSI B18.3.1M).
- Proof tested to 2.5 times the WLL.
- Fatigue rated to 1.5 times the WLL.
- Design Factor 4 : 1
- All YOKE Lifting points meet or exceed all the requirements of ASME B30.26.
- Quick and simple assembly, just a tapped hole is required.



Part Code	WLL tonnes	Thread			A mm	B mm	C mm	D mm	F mm	G mm	H mm	S mm	SW mm	Torque in Nm	Mass kg
		M mm	E mm	Pitch DIN13											
8-211-003	0.3	M8	11	1.25	30	35	35	10	85	55	29	6	13	30	0.2
8-211-006	0.63	M10	16	1.5	30	35	36	10	85	55	29	6	17	60	0.3
8-211-010	1.0	M12	18	1.75	33	37	44	14	98	57	36	8	19	100	0.5
8-211-012	1.2	M14	21	2	33	37	45	14	98	57	36	10	22	120	0.5
8-211-015	1.5	M16	24	2	33	37	46	14	98	57	36	10	24	150	0.5
8-211-020	2.0	M18	26	2	50	54	57	17	140	82	44	12	30	200	1.3
8-211-025	2.5	M20	30	2.5	50	54	57	17	140	82	44	12	30	250	1.3
8-211-040	4.0	M24	36	3	50	54	59	17	140	82	44	14	36	400	1.4
8-211-042	4.0	M27	38	3	60	65	79	23	170	99	62	17	41	400	2.8
8-211-050	5.0	M30	48	3.5	60	65	81	23	170	99	62	17	46	500	3.1
8-211-070	7.0	M36	54	4	60	65	88	23	178	99	65	22	55	700	3.3
8-211-080	8.0	M36	62	4	77	85	101	27	225	124	78	22	55	800	5.8
8-211-100	10.0	M42	72	4.5	77	85	104	27	225	124	78	24	65	1000	6.3
8-211-150	15.0	M42	63	4.5	95	104	112	36	256	158	86	24	65	1500	10.8
8-211-200	20.0	M48	72	5	95	104	120	36	259	158	90	27	75	2000	11.6

Bolt in GEOMET finish on request.