

Q-Check®

The tool for your quality assurance



GWK GmbH
In der Steinbach 2
55758 Schauren

Telefon: 06786 2904860
E-Mail: info@gwkgerlach.de
Internet: <https://gwkgelach.com>

Technical features

- Measuring range 3–1000 Nm
- Audit functions: Prevail torque / Loosen-tighten
- Further torque measurement for process capability analysis after VDI/VDE 2645-3
- Wireless data transfer WLAN
- Compatible with the analysis software Ceus and QS-Torque
- Intuitive graphical user interface
- 1D / 2D scanner
- 2 GB memory for up to 1,000 screw positions
- No worker influence for precise results
- optional upgrade to torque, angle and yield point process
- Activation for second measuring channel

Technical data

- Measuring accuracy torque
± 1% between (10 - 100)% of the nominal range
- Measurement accuracy rotation angle *
0.1° resolution of display
- Microprocessor, measured value memory
32 bit RISC architecture internal memory 2 GB
- TFT display
320 x 240 pixels, 16-bit colour analogue touch panel
- Power supply Li-ion, 2600 mAh with overload protection
for approx. 8 hours continuous operation

Q-Check ®



Dimensions Q-Check ®

Q-Check ® Dimensions without tool insert	30/30-L*	60/60-L*	100/100-L*	200	300	400	600	800	1000
Measuring range [N·m]	3 - 30	6 - 60	10 - 100	20 - 200	30 - 300	40 - 400	60 - 600	80 - 800	100-1000
Length [mm]	405 / 440*	415 / 450*	415 / 450*	545	825	825	1080	1440	1455
Width [mm]	79	79	79	79	79	79	79	79	79
Height [mm]	40	40	40	40	40	40	40	40	40
Weight [kg]	ca. 0,9	ca. 1,1	ca. 1,1	ca. 1,4	ca. 2,0	ca. 2,0	ca. 2,6	ca. 3,0	ca. 3,3
Square mount [mm]	9 · 12	9 · 12	9 · 12	14 · 18	14 · 18	14 · 18	14 · 18	14 · 18	22 · 28
Drive [mm]	3/8"	3/8"	1/2"	1/2"	1/2"	3/4"	3/4"	3/4"	1"
Reversible ratchet inside micrometre [mm]	17,5	17,5	17,5	25	25	25	30	44	153

* Housing for barcode scanner (* optionally available)

Overview

Q-Check[®]



* optionally available