

GEOMETRIE CUBE GRAVEL-BIKE NUROAD C:62 ONE

RAHMEN	C:62® Advanced Twin Mold Technology, Internal Cable Routing, Integrated Seat Post Clamp, Flat Mount Disc, Fender/Rack & Kickstand Option, 12x142mm, UDH
GRÖSSE	XS (50cm), S (53cm), M (56cm), L (58cm), XL (61cm)
GABEL	CUBE C:62® Technology, 1 1/8" - 1 1/2" Tapered, Integrated Cable Routing, Flat Mount Disc, Fender & Lowrider Mounts, Internal Light Cable Option, 12x100mm
BREMSANLAGE	Shimano GRX ST-RX610 / BR-RX410, Hydr. Disc Brake, Flat Mount (160/160)
SCHALTWERK	Shimano GRX RD-RX822-SGS, 12-Speed
SCHALT-/ BREMSGRIFFE	Shimano GRX ST-RX610
KURBELGARNITUR	SHIMANO GRX FC-RX610, 40T
KASSETTE	Shimano Deore CS-M6100, 10-51T
KETTE	SHIMANO CN-M6100
LAUFRADSATZ	Newmen Performance X.R.25, 28/28 Spokes, 12x100mm / 12x142mm, Tubeless Ready
REIFEN	SCHWALBE G-ONE R PRO, TLR, 45-622
VORBAU	CUBE CIS Stem w/ Cable Routing, FPI-Link
LENKER	Newmen Advanced Gravel Bar 318, Carbon, 31.8mm
LENKERBAND	ACID Bartape CC 3.0
SATTELSTÜTZE	Newmen Advanced, Carbon, 27.2mm
SATTEL	ACID Nuance Pro
STEUERSATZ	ACROS, Top Integrated 1 1/2" w/ Integrated Cable Routing, Bottom Integrated 1 1/2"
GEWICHT	9,3 kg
FARBE	blackline

GRÖSSE	XS-50cm	S-53cm	M-56cm	L-58cm	XL-61cm
SITZROHR	430	460	490	510	540
OBERROHR HORIZONTAL	522	537	560	575	592
SITZWINKEL	75,5	74,7	73,9	73	73
STEUERROHRWINKEL	69	70	71,5	72	72,5
KETTENSTREBEN	440	440	440	442	442
STEUERROHR	102	124	155	174	197
RADSTAND	1043	1044	1046	1048	1060
TRETLAGERHÖHE ZUR NABENACHSE	-70	-70	-70	-70	-70
ÜBERSTANDSHÖHE- 80mm	743	771	805	824	851
REACH	388	388	393	392	402
STACK	520	544	579	599	623
LAUFRADGRÖSSE	28	28	28	28	28

GRÖSSE	XS-50cm	S-53cm	M-56cm	L-58cm	XL-61cm
Länge Vorbau	80	90	100	100	110
Breite Lenker	400	420	420	440	440
Länge Kurbel	165	165	170	170	172,5
Länge Sattelstütze	350	350	400	400	400
Durchmesser Sattelstütze	27,2	27,2	27,2	27,2	27,2
Durchmesser Reifen maximal	728	728	728	728	728
Breite Reifen maximal	50	50	50	50	50

