

GEOMETRIE CUBE NUROAD HYBRID C:62 SLX 400X

RAHMEN	C:62® Advanced Twin Mold, Gravel Endurance Geometry, Advanced Internal Cable Routing, Flat Mount Disc, Fender/Rack & Kickstand Option, Boost 148, UDH™, Fixed Integrated Battery
GRÖSSE	XS (50cm), S (53cm), M (56cm), L (58cm), XL (61cm)
BREMSANLAGE	Sram Rival HRD, Hydr. Disc Brake (180/180)
SCHALTWERK	Sram GX Eagle AXS™ Transmission, 12-Speed, Electronic Shifting System
SCHALT-/ BREMSGRIFFE	Sram Rival eTap AXS™
KURBELGARNITUR	e*thirteen Helix Race Alloy e*spec Crank, 42T
KASSETTE	Sram XS-1275, 10-52T
KETTE	Sram GX Eagle™ Transmission
LAUFRADSATZ	Newmen Evolution SL X.R.25
REIFEN	Schwalbe G-One Bite Evo, SuperGround, Kevlar, 45-622
SATTEL	Natural Fit Nuance
SATTELSTÜTZE	Newmen Advanced, Carbon, 27.2mm
AKKU	Bosch CompactTube 400
MOTOR	Bosch Drive Unit Performance SX (55Nm) Cruise (250 Watt), Smart System
KETTENFÜHRUNG	Reverse Flip-Guide E-Chain Guide, Direct Mount, I-Plate
VORBAU	CUBE CIS Stem w/ Cable Routing
REMOTE	Bosch System Control, incl. Mini Remote
STARRGABEL	CUBE C:62® Technology, 1 1/2" - 1 1/2" Tapered, Flat Mount Disc, Fender & Lowrider Mounts, 12x100mm
LENKERBAND	ACID Bartape CC 3.0

GRÖSSE	XS-50cm	S-53cm	M-56cm	L-58cm	XL-61cm
SITZROHR	430	460	490	510	540
OBERROHR HORIZONTAL	522	537	560	575	592
SITZWINKEL	75,5	74,7	73,9	73	73
STEUERROHRWINKEL	69,5	70,5	71,5	72	72,5
KETTENSTREBEN	453	453	453	453	453
STEUERROHR	95	112	145	164	187
RADSTAND	1053	1052	1059	1060	1072
TRETLAGERHÖHE ZUR NABENACHSE	-70	-70	-70	-70	-70
ÜBERSTANDSHÖHE- 80mm	740	773	804	825	857
REACH	387	388	393	392	402
STACK	524	544	579	599	623
Länge Sattelstütze	350	350	350	350	350
Durchmesser Sattelstütze	27,2	27,2	27,2	27,2	27,2
Länge Kurbel	165	165	165	170	170
Durchmesser Reifen maximal	728	728	728	728	728
Breite Reifen maximal	50	50	50	50	50
Länge Vorbau	80	80	90	100	100
Breite Lenker	420	440	440	460	460

