

TOP-1000

Non-Contact Tonometer with Pachymetry

By combining soft air puffing, 3D auto-tracking and a Scheimpflug camera, the TOP-1000 delivers excellent IOP measurements corrected for central corneal thickness.

Excellent features

- + 3D auto-tracking
- + Auto-measurement
- + Soft air puffing
- + Pachymetry for IOP correction
- + Excellent measurement repeatability
- + Friendly user interface on 10.1" touch screen
- + Patient database



Specifications

INTRAOCULAR PRESSURE MEASUREMENTS	
Measurement range	1 mm to 60 mm Hg
Measurement range setting	Auto/30 mm Hg/60 mm Hg
Measurement principle	Air puff method
Display units	mm Hg/hPa
Working distance	11 mm

CENTRAL CORNEAL THICKNESS MEASUREMENT	
Measurement range	400 μ m to 800 μ m
Measurement principle	Slit image on central cornea
Light source	Blue LED

MAIN UNIT	
Measurement mode	Fully automatic/Automatic/Manual
Alignment	Fully automatic 3D tracking
Chin rest	Motorised
Display	10.1" LCD touch screen
Printer	Thermal line printer with auto-cutter
Fixation target	Internal LED fixation light
Operation movement range	Front/Back: 40 mm Left/Right: 90 mm Up/Down: 30 mm
Chin rest movement range	Up/Down: 70 mm
Interface	USB, RS-232, LAN

DIMENSIONS AND ELECTRICAL REQUIREMENTS	
Dimensions WDH	282 mm x 500 mm x 500 mm
Weight	17 kg
Voltage	100 VAC to 240 VAC
Frequency	50/60 Hz

TOMEY EUROPE
TOMEY GMBH



[tomey.de](https://www.tomey.de)

TOMEY GmbH is the European headquarter of TOMEY Corporation,
2-11-33 Noritakeshinmachi Nishi-Ku, Nagoya, 451-0051, Japan

2025/07 – subject to change without notice

Always read and follow the instructions for use.
Not all products, services or offers are approved or offered in every market. Please note that the current status of approval for the labelling, instructions and contents of the brochure may vary from one country to another.

