TRU-1000 Refraction Unit

A good combination of comfort, elegance and functionality. Our TRU-1000 offers a high degree of flexibility and convenience with a remarkably compact footprint. Its modern and plain design fits into small examination rooms.

Excellent features

- + Space-saving
- + Preconfigured for TOMEY equipment
- + Easy to install (right or left side)
- + Timeless and modern design



Specifications

FEATURES	
Table	Rotating 90°, laterally movable, for 2 devices
Table height adjustment	Not available
Table lock	Magnetic
Max. load capacity (table)	50 kg
Patient chair	ER-3000
Patient chair elevation	200 mm
Max. load capacity (chair)	150 kg
Projector column height	approx. 1700 mm
Connectors	2x power outlet (230 V) 1× RS-232, 1× 6-pin (6 V / 12 V), 1× USB 2.0
Reading light	Cold white LED 12 V
Internal light	Cold white LED 12 V

ELECTRIC REQUIREMENTS & WEIGHT	
Power consumption	280 VA
Power supply	110 V AC/115 V AC/230 V AC ±10 %
Total weight (incl. chair)	approx. 250 kg

DIMENSIONS	
Width	max. 1300 mm (±10 mm)
Height	max. 1750 mm (±10 mm)
Depth	max. 1820 mm (±10 mm)
Table	870 mm x 440 mm (±5 mm)

OPTIONAL	
	PA-1000 Phoropter arm "balance"
	PA-3000 Phoropter arm "linear"
Optional equipment	SH-1000 Skiascope/Ophthalmoscope holder
	TC-1000 Trial lens cabinet
	CBS-1000 Control box stand



TOMEY EUROPE TOMEY GMBH

tomey.de

TOMEY GmbH is the European headquarter of TOMEY Corporation, 2-11-33 Noritakeshinmachi Nishi-Ku, Nagoya, 451-0051, Japan

2025/07 - subject to change without notice

Always read and follow the instructions for use.

Not all products, services or offers are approved or offered in every market. Please note that the current status of approval for the labelling, instructions and contents of the brochure may vary from one country to another.

