Stories

SELECT THE PERFECT COLOUR FOR YOUR TIMBER WEATHERBOARDS







THE GOOD NEWS

Envira weatherboards and components are machine coated on all faces with an alkyd true primer ready for two top coats of premium quality house paint.

FUTURE PAINTING

As with any painted cladding if the surface is well prepared, painted and maintained then re-painting is only required every 10 to 12 years.

NIAGARA STRENGTH IN TIMBER

Envira Weatherboard System is a quality building product by Niagara

KEEP IT COOL

Using dark paint colours on any surface can generate excessive heat. To safeguard against this select a paint with a 45+ light reflectance value (LRV) rating.

FOLLOW THE RULES

All preparation and painting must meet the current requirements of AS/NZS 2311 Guide to Painting of Buildings and the paint manufacturer's data sheet.

PAINT FOR LONGEVITY

Use a qualified painter and select a quality paint with a gloss level of 10 per cent or more. Apply the first top coat prior to installation and the second within six weeks following installation.

FIND OUT MORE

Refer to Section 4 of our Technical Manual and Installation Guide, which covers Painting and Maintenance or contact our friendly team at Niagara with any questions.

Please Note: Paint Colours may vary slightly from swatches printed in this booklet. Always view a physical swatch before making your final choice at your local Resene Colorshop www.resene.co.nz/colorshops



Resene Half Spanish White



Resene Tea cc

Resene Half Truffle cc

Resene Half Napa co

Resene Cloud cc

Resene Quarter Pravda cc Resene Akaroa cc



Resene Eighth Lemon Grass cc Resene Half Lemon Grass co



Resene Duck Egg Blue Resene Half Duck Egg Blue Resene Quarter Duck Egg Blue

Resene Breathless cc

Resene Link Water

Resene Oxygen cc



Resene Silver Chalice cc

Resene Gool Golours TM

Resene's CoolColour™ range allows for the use of slightly darker paint colours than typically recommended. Paint suppliers will advise on suitable colours for timber.

Resene recommends these CoolColours™ for use on Envira Timber Cladding as they all have a total solar reflectance (TSR) rating of 40% or more.



