






GEN 5

All Platform Configurations

Configuration									
	Foundation 110	Prelude 230	Prelude 232	Prelude 430	Prelude 432	Nemesis 630	Nemesis 632	Nemesis 830	Nemesis 832
Hosting ¹	-	4 VM	4 VM	6 VM	6 VM	4 VM	4 VM	6 VM	6 VM
High Availability	-	-	-	-	-	✓	✓	✓	✓
Order Reference	F110	P230	P232	P430	P432	N630	N632	N830	N832
Hardware	Compact industrial chassis	1U Server	1U Server	2U Server	2U Server	2U Cluster + Quorum Appliance	2U Cluster + Quorum Appliance	4U Cluster + Quorum Appliance	4U Cluster + Quorum Appliance
CPU	4-Core	8-Core	8-Core	24-Core	24-Core	8-Core	8-Core	24-Core	24-Core
RAM	8 GB	64 GB	64 GB	64 GB	64 GB	64 GB	64 GB	64 GB	64 GB
Storage	512 GB M.2 SATA SSD	960 GB Redundant SSD	960 GB Redundant SSD 7.2 TB Redundant HDD	1.92 TB Redundant SSD	1.92 TB Redundant SSD 24 TB Redundant HDD	960 GB Redundant SSD	960 GB Redundant SSD 7.2 TB Redundant HDD	1.92 TB Redundant SSD	1.92 TB Redundant SSD 24 TB Redundant HDD
Network	2 x 1 GB PoE PD Input	4 x 1 GB 4 x 10 GB	4 x 1 GB 4 x 10 GB	4 x 1 GB 4 x 10 GB	4 x 1 GB 4 x 10 GB	4 x 1 GB 4 x 10 GB 2 x 25 GB SFP 28 Interconnect³	4 x 1 GB 4 x 10 GB 2 x 25 GB SFP 28 Interconnect³	4 x 1 GB 4 x 10 GB 2 x 25 GB SFP 28 Interconnect³	4 x 1 GB 4 x 10 GB 2 x 25 GB SFP 28 Interconnect³
Modules ²	2	4	4	6	6	6	6	10	10
Users ²	5	5	20	20	50	20	50	50	200

1. These are recommended values only. Results may vary depending on usage environment and hosted systems requirements. 2. Modules and Users license provided with the related model. Additional Modules and/or Users license can be added at time of order, or at any time in the future. 3. These ports are reserved for internal system use. The standard warranty is 3 years but can be extended to 5 years as part of the optional ISAAC Extended Coverage package.



isaacplatform.com

info@isaacplatform.com