

Traglasttabelle in t
 Maschine abgestützt 7.2 m



GMK 4100L-2
 6.8 t Gegengewicht

Arbeits- radius in m	Hauptauslegerlängen in m										
	19.60	23.70	27.80	31.80	35.70	39.10	42.60	45.80	49.50	56.10	60.00
3.0	74.5										
4.0	63.0	62.5									
5.0	54.0	49.5	46.0	37.5							
6.0	41.0	38.0	36.5	33.0	31.0						
7.0	32.5	31.5	29.0	28.0	26.0	24.0					
8.0	27.0	25.5	23.5	23.5	21.5	19.9	18.9				
9.0	22.5	21.5	19.7	19.6	19.2	16.8	16.0	15.9			
10.0	18.9	19.1	16.7	17.0	16.8	14.3	13.7	14.5	13.1		
11.0	16.7	16.5	14.6	15.7	14.6	13.3	11.8	13.0	12.7	9.9	
12.0	14.3	14.4	13.6	13.8	12.9	12.5	11.0	11.5	11.5	9.9	8.1
13.0	12.3	12.6	12.8	12.3	11.4	11.6	10.3	10.2	10.7	9.1	8.1
14.0	10.6	11.0	11.6	11.0	10.2	10.7	9.7	9.1	9.6	8.3	7.6
15.0	9.3	10.0	10.2	9.8	9.1	9.7	9.1	8.2	8.6	7.4	6.8
16.0	8.2	9.0	9.0	9.2	8.2	8.7	8.3	7.3	7.8	6.7	6.0
18.0		7.1	7.3	7.6	6.9	7.2	6.8	5.9	6.4	5.4	4.8
20.0		5.8	6.0	6.2	6.2	6.0	5.7	4.8	5.3	4.4	3.8
22.0			4.9	5.1	5.1	5.0	4.8	3.9	4.4	3.5	3.0
24.0			4.0	4.3	4.2	4.1	4.0	3.2	3.7	2.8	2.3
26.0				3.5	3.5	3.4	3.3	2.6	3.1	2.2	1.8
28.0				2.9	2.9	2.8	2.7	2.0	2.5	1.7	1.3
30.0				2.3	2.4	2.3	2.2	1.5	2.0	1.3	
32.0						1.8	1.8	1.1	1.6	0.9	
34.0						1.5	1.4		1.2		
36.0						0.9	1.0		0.9		