

G2

This small edge device is purpose-built for compact digital signage setups, delivering reliability and performance in a space-saving form factor.



KEY FEATURES

DIGITAL SIGNAGE

Ideal for smaller digital signage applications that needs a small form factor

AUDIO SERVER

Great option for a small audio server via Dante Virtual soundcard integration

LED SERVER

Excellent choice for a small LED server, due to Realmotion DMX integration

OUTPUTS


Up to 1 × 4K display or 3 x FHD in lossless codecs

CERTIFICATION

Certified for all major international safety and emissions standards

INCLUSIONS

3 year hardware warranty included
Perpetual Realmotion license included



LEGEND

1 Power supply outlet (130W)

3 4 x USB-A 3.2

5 Ethernet (5GB)

2 3 x DP 1.4a

4 USB-C 3.2

6 Ethernet (1GB)

REALMOTION G-SERIES

G2

HARDWARE

| | |
|-----------------|---|
| Form factor | Micro |
| Graphics | Intel graphics |
| Processor | Intel Core Ultra 14 cores 3.5 GHz - 5.0 GHz |
| RAM | 32 GB DDR5 |
| Boot drive | 1TB Gen 4 PCIe NVMe |
| Data drive | N/A |
| RAID controller | No |
| Front USB ports | 1 x USB C (3.2 gen 2) 2 x USB A (3.2 gen 2) |
| Rear USB ports | 1 x USB C (3.2 gen 2) 2 x USB A (3.2 gen 2) 2 x USB A (3.2 gen 1) |
| Ethernet | 2 x RJ45 (1GB + 5GB) |
| Wireless | Wi-Fi 6E + Bluetooth 5.3 |
| Video ports | 3 x Displayport 1.4a |
| Audio port | Audio jack 1.8mm |

SOFTWARE

| | |
|------------------------|--------------------------------|
| Realmotion Engine | Perpetual license included |
| OS | Windows 11 IoT Enterprise LTSC |
| Audio (optional) | Dante virtual soundcard |
| Interactive (optional) | N/A |

OPTIONAL EXPANSIONS

| | |
|----------------------|-----|
| HDMI (video capture) | N/A |
| SDI (video capture) | N/A |
| Genlock | N/A |
| Audio | N/A |

* Not all optional expansions are possible at the same time. Contact us for more information.

ELECTRICAL & OPERATING

| | |
|--------------------------|---|
| Line voltage | 100 - 240 VAC |
| Frequency | 50 - 60 Hz |
| Power supply | 130W |
| Operating temperature | 10°C to 35°C (50°F to 95°F) |
| Operating humidity range | 20% to 80% (non-condensing) |
| Storage temperature | -40°C to 65°C (-40°F to 149°F) |
| Storage humidity range | 5% to 95% (non-condensing) |
| PSU certification | UL (North America) CE (Europe) UKCA (UK) PSE (Japan) CCC (China) BIS (India) |

* Only main PSU certification standards are listed. Contact us if your standard is not listed.

WARRANTY & SECURITY

| | |
|-----------------------|--|
| Warranty | 3 years standard warranty included |
| Optional warranty | 5 years |
| Regulatory compliance | CEC MEPS WEEE Japan Energy Law EU RoHS China RoHS |

* Only main regulatory compliance standards are listed. Contact us for more information.

CHASSIS

| | |
|--------------------|---|
| Weight | 3.15 lbs (1.43 kg) |
| Dimensions (H/W/D) | 1.42" (36 mm) 7.17" (182 mm) 7.01" (178 mm) |
| Rack unit | 1U |
| Rack mountable | N/A |

CONTACT US AT INFO@REALMOTION.COM FOR A QUOTE