



Safeguard Shipments with Real-Time Threat Detection



REAL-TIME TAMPER DETECTION

When cut or damaged



TOP-LEVEL COMPLIANCE

ISO 17712 High Security Certified & C-TPAT compliant



MULTI-LAYERED SECURITY

Layer alerts for extra protection



INSTANT LOCATION ALERTS

Quickly locate & secure cargo

Seal It. Track It. Protect It.

The Tive™ Security Seal is a single-use, high-security cable seal that provides real-time threat detection to help teams protect containers and trailers. Paired with a Tive Solo 5G tracker, Tive sends an alert when the Seal is cut or damaged, giving you the visibility to respond quickly and keep high-value shipments secure from origin to delivery.

Key features of the Tive Seal include:

- › **Seal cut alerts:** Get alerts when the Seal is cut
- › **Separation alerts:** Notifies you when a Solo 5G tracker loses connection with a paired Tive Seal, signaling removal or destruction
- › **Light alerts:** Detect unplanned door openings or exposure to light that could indicate unauthorized access or potential break-ins
- › **Connectivity alerts:** Get notified when a Tive Solo 5G tracker loses connectivity, which may indicate GPS jamming or interference
- › **Prolonged stop & route deviation alerts:** Flag extended stops in risky areas and deviations from expected routes so teams can act before issues escalate
- › **Compliance & investigation support:** The Tive Seal is ISO 17712 High Security Certified and C-TPAT compliant, with a full digital audit trail to support investigations and prove chain of custody



Designed for these shipments



Automotive



Electronics



Luxury Goods



Perishables



Retail



Technical Specifications

COMPATIBLE TIVE TRACKERS

Solo 5G (TT-7000 & TT-7100)

CONNECTIVITY

Wireless protocol: Wide band 2.4GHz

Wireless range: 75 m (250 ft) line of sight

Seal data transmitted in real time with Tive Solo 5G (TT-7000, TT-7100)

OPERATING TEMPERATURE

-30°C to 50°C (-22°F to 122°F)

BATTERY

CR2025 (3 volt; non-rechargeable)

Battery life: 4 months after activation

Shelf life: 12 months

CASE SPECIFICATIONS

Case Material:

UL 94-V0 plastic; UV protected

Dimensions:

1.5 in x 2.2 in x 0.7 in

(37 mm x 57 mm x 19 mm)

Weight:

1.9 oz (53g)

IP Rating:

IP67

Cable length:

12 in

CERTIFICATIONS

FCC, NOM, IC, CE, PROP65, RoHS 2.0

The Tive Seal is 17712 High Security Certified & C-TPAT compliant

The Tive solution is fully compliant with SOC 2 Type 2 & ISO/IEC 27001:2022

The Tive Seal is ISO 17712 High Security Certified & C-TPAT compliant

Get Real-Time Tamper Detection.

Learn more at www.tive.com/securityseal