



- 1: INPUT (JACK) Connect your bass here.
- 2: OUTPUT (JACK) Connect a cord out to your amplifier here.
- 3: 18 VDC 60 mA (JACK) 2.1mm barrel jack, with the center negative for connecting an 18 Volt DC regulated supply, 60 mA capacity or greater with a center negative plug. The Whirlwind PS18EFX (included) is recommended for proper operation.
- 4: ATTACK (SWITCH) Switches between three pre-defined attack rates. FAST causes the effect to kick in almost instantaneously, MED allows some of the note's initial attack to come through before the effect kicks in and SLOW allows even more of the initial attack to come through.
- 5: OUTPUT LEVEL (KNOB) Controls the over all volume of the pedal.
- 6: LIMIT/COMPRESS (SWITCH) Switches between Compression and Limit mode. Compression gently evens out the louder and softer levels in the signal and helps the bass "sit in the mix". Think of limiting as a more aggressive form of compression with a flavor all its own. Experiment!
- 7: INPUT GAIN (KNOB) Controls how much compression / limiting is applied to the signal. Adjusting this control changes the overall volume of the effect. Use the OUTPUT LEVEL knob to match or even increase the overall volume feeding your amp.
- 8: GAIN REDUCTION (LEDs) Displays the amount of limiting/compression in dBs.
- 9: ON/OFF (FOOTSWITCH) Engages and disengages the effect. When engaged, the LED above the footswitch will illuminate.



Warranty:

This product is warranted to be free of defects in materials or workmanship to the original purchaser for a period of 2 years from the date of purchase. Should warranty service be required, return the unit postage paid along with the original sales receipt to:

Whirlwind Music Dist., Inc. 99 Ling Road Rochester NY 14612 Whirlwind will, at its option, repair or replace the unit. This warranty does not cover damage resulting from abuse, unauthorized modifications or use of the product in unintended applications.

HAND MADE IN THE USA

www.whirlwindusa.com • 800-733-9473