



PRECAST/TILT UP

X-FOOT FERRULE SPECIFICATION SHEET

All CANZAC Ferrules are manufactured and tested to comply with the requirements of AS 3600 and AS 3850. Our high-quality metric threaded inserts meet all requirements for permanent and temporary connections using Grade 4.6 Metric Bolts.

M12 to M20 threaded ferrules are a nominal 28.0mm OD with the M24 threaded ferrule having a 32mm outside diameter. The nominal 15mm diameter clearance hole is provided for the N12 tension bar.

PRODUCT CODE	FERRULE SIZE	INSTALLATION DETAILS		MINIMUM DIMENSIONS		LENGTH	OUTSIDE DIA. (mm)	BOX QTY
		CROSS HOLE TO SUIT	TIGHTENING TORQUE,	MIN. ELEMENT THICKNESS (mm)	MIN. EDGE DISTANCE IN LOAD DIRECTION (mm)			
92 205	M12 x 50	N8	30	75	150	50	20	50
92 211	M12 x 75	N12	30	105	150	75	28	50
92 231	M12 x 96	N12	30	120	150	96	28	50
92 216	M16 x 75	N12	75	105	150	75	28	50
92 236	M16 x 96	N12	75	120	150	96	28	50
92 221	M20 x 75	N12	143	105	150	75	28	50
92 241	M20 x 96	N12	143	120	150	96	28	50
92 246	M24 x 96	N12	250	120	150	96	32	50