

CANZAC® | GROUP

Improving the performance of concrete worldwide®



CURING SYSTEMS

SINAK 102 CURING

BETTER THAN WATER CURING

S-102™ is formulated to exceed the performance requirements of all concrete water-cure specifications. Use of S-102™ assures that the specified design strengths will be achieved along with development of improved surface durability properties. S-102™ leaves no surface residue and is guaranteed to be compatible with all bond-breakers, patching compounds, wall coatings, paints, flooring materials, staining processes, crack and joint materials. Overspray on reinforcement steel does not require removal.

INFORMATION

Compatible with all bond-breakers, patching compounds, wall coatings, paint, flooring materials, staining processes, and crack and joint materials. Over spray in reinforcement steel does not require removal. It is fast and easy to apply, doesn't form a film and leaves no surface residue.

SINAK S-102™ is an environmentally friendly, water-based liquid with a proprietary formula in solution. It requires no mixing, diluting or agitating.

Color: water clear;
Specific Gravity: 1.1;
Net Weight per gal: 9.2 lbs;
Dry Solids Content (by weight): 11.1%;
Flash Point: none;
Toxicity: non-toxic;
VOC: contains NO volatile organic compounds or solvents.

PRODUCT HANDLING & STORAGE

S-102™ has an indefinite shelf life but must be kept in tightly secured containers to prevent evaporation and contamination. SINAK S-102™ MUST be protected from freezing. Product that has frozen will not function as intended.

See product label or product information sheets for complete application instructions and precautions.

KEY FEATURES

- Fast & easy to apply
- Non film forming
- Eliminates cure-related cracking
- Compatible with all topically applied materials

APPLICATIONS

- Areas to receive applied finishes
- Cast in place walls & columns
- Superflat floors
- Pre-cast concrete
- Parking structures
- Road/bridge/runway pavements
- Tilt-up construction
- Shotcrete/lightweight concrete
- Warehouse floors to receive polishes

| CODE | DESCRIPTION | UNIT |
|--------|-----------------------------|------------|
| 21 120 | SINAK S-102 CONCRETE CURING | 18.9L PAIL |
| 21 122 | SINAK S-102 CONCRETE CURING | 1040L TOTE |

CANZAC®
Under Slab - In Slab - On Slab

LESA
SYSTEMS
ENGINEERED CONCRETE FLOOR SYSTEMS

MONSTA-SLAB

converge

ROMBUS
INDUSTRIES

CANZAC® LTD
Concrete Lifting Systems®

0800 422 692 | www.canzac.com