

## STEGOTACK™ TAPE

A STEGO INDUSTRIES, LLC INNOVATION | VAPOUR RETARDERS 07 26 00, 03 30 00 | VERSION: 28 JAN 2025

### 1. PRODUCT NAME

STEGOTACK TAPE

### 2. MANUFACTURER

Stego Industries, LLC  
216 Avenida Fabricante, Suite 101  
San Clemente, CA 92672 USA  
Sales, Technical Assistance  
Ph: +1 (877) 464-7834  
international@stegoindustries.com  
[stegoindustries.com](http://stegoindustries.com)



### 3. PRODUCT DESCRIPTION

**USES:** StegoTack Tape is a double-sided adhesive strip used to bond and seal Stego™ Wrap, StegoHome™, and StegoCrawl™ Wrap to concrete, masonry, many foam insulation materials, metal, and other surfaces.

**COMPOSITION:** StegoTack Tape is made from a blend of synthetic rubber and resins.

**SIZE:** StegoTack Tape is 51 mm x 15 m (2" x 50'). StegoTack Tape ships 12 rolls in a case.

#### FEATURES AND BENEFITS:

- Highly flexible and moldable
-  Low VOC Emissions - Certified Clean Air GOLD
- Made in the USA



The versatility of StegoTack Tape makes it an excellent option for Stego Wrap, StegoHome, and StegoCrawl installation applications.

### 4. TECHNICAL DATA

TABLE 4.1: PHYSICAL PROPERTIES OF STEGOTACK TAPE

PROPERTY	RESULTS	
Dimensions	51 mm x 15 m (2" x 50')	
Total Thickness	0.76 mm (30 mil)	
Permeance (30 mil)	1.7 ng/(m <sup>2</sup> *s*Pa)	0.03 gr/(ft <sup>2</sup> *hr*in-Hg)
Color	Grey	
Material	Synthetic rubber blend	
Adhesion to Steel	2.19 kN/m (12.5 lb/in) width ASTM D1000	
Installation Temperature	4°C/43°C (40°F/110°F)	
In Service Temperature Range	-29°C/60°C (-20°F/+140°F)	
VOC Content	No VOCs, 100% solids	

## STEGOTACK™ TAPE

A STEGO INDUSTRIES, LLC INNOVATION | VAPOUR RETARDERS 07 26 00, 03 30 00 | VERSION: 28 JAN 2025

### 5. INSTALLATION

**TO WALLS:** Make sure the area of adhesion is free of dust, dirt, debris, moisture, and frost to allow maximum adhesion. Remove release liner on one side and stick to desired surface. When ready to apply the vapour barrier or retarder, remove the exposed release liner and press the vapour barrier or retarder firmly against StegoTack Tape to secure.

Cut StegoTack Tape using a utility knife or scissors. Cut StegoTack Tape before removing the release liner for easier cutting.

Install StegoTack Tape between 4°C and 43°C. Do not exceed 7 days between StegoTack Tape installation and concrete placement or full protection from UV and weather exposure.

For additional information please refer to Stego's complete installation instructions.

### 6. AVAILABILITY & COST

StegoTack Tape is available through our network of building supply distributors. For current cost information, contact your local Stego™ distributor or Stego Sales Representative.

### 7. WARRANTY

Stego believes to the best of its knowledge, that specifications and recommendations herein are accurate and reliable. However, since site conditions are not within its control, Stego does not guarantee results from the use of the information provided herein. Stego does offer a limited warranty on StegoTack Tape. Please see [stegoindustries.com/legal](https://stegoindustries.com/legal)

### 8. MAINTENANCE AND STORAGE

**Maintenance:** Check post-application. Replace or overlay areas that show wear.

**Storage and Handling:** Store in original packaging in cool, dry conditions. Ensure surfaces for application are clean for best adhesion.

Please refer to the Safety Data Sheet (SDS) for detailed safety, storage, and handling procedures.

### 9. TECHNICAL SERVICES

Technical advice, custom CAD drawings, and additional information can be obtained by contacting Stego or by visiting the website.

**Email:** [international@stegoindustries.com](mailto:international@stegoindustries.com)

**Contact Number:** +1 (877) 464-7834

**Website:** [stegoindustries.com](https://stegoindustries.com)

### 10. FILING SYSTEMS: [stegoindustries.com](https://stegoindustries.com)