

CANZAC® | GROUP

Improving the performance of concrete worldwide®



FORMWORK SYSTEMS

DUALCAST

THE SMARTER, STRONGER, GREENER CHOICE

Dualcast is the game-changing UPVC Concrete Screed Rail System that allows you to form Durable Construction joints faster than ever before.

Dualcast provides you with confidence that the formwork can be set as close as possible to the specified slab thickness (no big gaps underneath the bottom of the joint) , that can effect structural integrity, and can also lead to differential settlement at the joint face.

Covering all common slab thicknesses from 85mm to 225mm, Dualcast eliminates the need to support the joint on concrete dabs. Our system ensures you achieve a durable ,full depth construction joint everytime.

Engineered for versatility, Dualcast rails are compatible with all types of screeds including Roller screeds & Vibrating screeds. The Patented design includes a removable top strip for joint sealing, while unique end clips enable fast and seamless setup.









In addition to saving time and money, it is a sustainable solution, Manufactured using recycled UPVC, it helps reduce plastic waste while delivering exceptional performance. Choosing Dualcast means building smarter, greener, and more efficiently.

KEY FEATURES

- Full depth construction joint every time
- Fast & easy installation
- No removal required
- Removable top strip
- Click-together design
- Reduces labour costs
- Sustainable & Eco friendly

APPLICATIONS

- Commercial flooring
- Petrol station forecourts
- Agricultural flooring
- Yard slabs
- Pavements
- Civil engineering projects

PRODUCT	CODE	DESCRIPTION	UNIT
	65 178	DUALCAST BASIC RAIL 75mm x 2.4m LENGTH REQUIRES TOP STRIP 10/20	2.4m LENGTH
	65 170	DUALCAST BASIC RAIL 125mm x 2.4m LENGTH REQUIRES TOP STRIP 10/20	2.4m LENGTH
	65 176	DUALCAST 10mm x 10mm x 2.4m REMOVABLE REBATE TOP STRIP	2.4m LENGTH
	65 179	DUALCAST 20mm x 10mm x 2.4m REMOVABLE REBATE TOP STRIP	2.4m LENGTH
	65 175	DUALCAST EXTENDER 25mm x 2.4m	2.4m LENGTH
	65 180	DUALCAST RAIL 125mm - SLOTTED FOR PLATE DOWELS ON 500oc 2.4m REQUIRES TOP STRIP 10/20	2.4m LENGTH
	65 172	DUALCAST JOINERS	EACH
	65 173	DUALCAST FIXING PIN 200mm	EACH

CANZAC®
Under Slab - In Slab - On Slab

LESASYSTEMS
ENGINEERED CONCRETE FLOOR SYSTEMS

MONSTA-SLAB

converge

ROMBUS
INDUSTRIES

CANZAC® LTD
Concrete Lifting Systems®

0800 422 692 | www.canzac.com