

T350V-50**PRODUCT NAME**

T350V-50

NOMINAL VOLTAGE

354 V

CAPACITY

150 Ah

ENERGY

52 kWh

**T350V-50**

1,361 x 772 x 286 mm

LITHIUM-ION BATTERIES FOR COMMERCIAL AND INDUSTRIAL APPLICATIONS

The **Proliance Intelligent Battery Series**® delivers rugged, reliable, and intelligent lithium-ion battery packs built for the most demanding commercial and industrial applications. Designed and assembled in the USA, Proliance batteries provide true drop-in replacement capability, advanced safety protections, and smart connectivity—all within a durable, high-performance design.

APPLICATIONS

- ✓ Commercial electric vehicles
- ✓ Construction
- ✓ Agriculture
- ✓ Mining
- ✓ Recreational & specialty
- ✓ ... and more!

**American Battery Solutions, Inc.**www.americanbatterysolutions.com+1 (248) 462-6364 | sales@americanbatterysolutions.com

KEY FEATURES

BUILT TO LAST

- ✓ Automotive-grade lithium-ion tech; rugged design

SCALABLE AND MODULAR

- ✓ Can be connected in parallel to meet higher energy requirements

SMARTER BATTERY


- ✓ Integrated liquid cooling and state-of-the-art BMS help to regulate battery performance

REAL-WORLD READY

- ✓ Wide operating temperature range; IP67 & IP69k enclosure

BUY AMERICA

- ✓ Designed, tested, and assembled in MI and OH USA



SPECIFICATION	T350V-50
Nominal ratings at 25 °C	354 V, 150 Ah, 52 kWh
Voltage range	288 V – 394 V
Cycle life at 25 °C, 80% SOH	2,500 cycles
Continuous current – charge	101 A
Continuous current – discharge	180 A
Peak current	Charge: 170 A Discharge: 490 A
Dimensions	1,361 x 772 x 286 mm
Weight	322 kg
Operating temperature range	Charge: 1 °C to 60 °C Discharge: -29 °C to 59 °C
IP rating	IP67 & IP69k
Cell technology	21700 NMCA Lithium-Ion

© 2026 American Battery Solutions, Inc. All rights reserved. This data sheet is for general informational purposes only and does not constitute a contract or warranty. Final product specifications, certifications, configurations, and availability may vary by application. Performance characteristics are dependent on use conditions. For the most current technical data, certifications, and application-specific guidance, please contact ABS directly.