



DRYING

FD-30 TP2 30LB CAPACITY ADVANCE DRYER



Fagor commercial dryers are perfect for laundromats, hotels, hospitals, nursing homes, and more.

TOUCH PLUS CONTROL

- 7" touchscreen – intuitive and completely programmable
- USB Connection: software free of charge
- 37 languages, continually expanding
- Upload videos to display, use for ads, instructions, etc.

CONNECTIVITY

- FagorKonnnect, standard
- Provided at NO extra charge
- Manage your laundry operations from anywhere, 24/7
- Remote diagnosis and technical service
- Create programs, special promotions, access real-time reports, have service alerts go directly to technicians, and more

OUTSTANDING FEATURES

- Reversing drum action, standard
- Stainless steel drum, standard
- Frequency inverter, standard

EFFICIENCY

- Intelligent humidity control with temperature control at drum air inlet
- Optimized, mixed airflow
- Full thermal insulation of the cabinet and double door glass

VERSATILITY

- Make to order – customization
- Easily converts from OPL to COIN
- Wetcleaning configuration

ERGONOMICS

- Stainless steel mesh lint filter
- Large loading doors

MAINTENANCE

- Hinged front control panel – easy and ergonomic access
- Complete technical menu
- Common parts across all models

MORE INFO


- Grey skin plate front and side panels, stainless look, standard
- Stainless steel drum, standard
- Soft touch hole design in dryer cylinder
- Anti-wrinkle at end of cycle
- ETL Approved

OPTIONS

- Integrated Fire Extinguishing System
- Dosing/spray system
- iDry - Intelligent humidity control with auto-dry capability (coin and OPL)
- Lint filter with various grids
- Stainless steel front panels
- Reversible door
- Heating options, natural gas and propane
- Tropicalized model: protected board
- Coin/token kit

TECHNICAL DATA
ADVANCE DRYER | FD-30 TP2

FD-30 TP2		
DRUM		
Load capacity	lbs	30
Drum diameter	in	29.53
Drum depth	in	24.02
Drum volume	cu. ft.	9.53
Door opening diameter	in	22.60
Height from floor to bottom of door	in	38.43
Drum motor power	hp	0.5
GAS POWER		
Installed heating power gas	Btu/h	69,983
Evaporation capacity	Gal/h	4.1
Gas inlet	in	1/2"
VENTILATION		
Normal air flow	cfm	706
Vent size	in	8"
Fan motor power	hp	0.34
CONNECTIONS		
Voltage 110-120/60/1~ +G	FLA/A	8.4/20
DIMENSIONS / PACKING DIMENSIONS		
Net width / Gross width	in	30.91 / 34
Net depth / Gross depth	in	38.96 / 42
Net height / Gross height	in	66.69 / 72
Net weight / Gross weight	lbs	397 / 419



- 01. Power supply
- 02. Fumes output Ø200
- 03. Gas inlet 1/2"
- 04. Steam inlet 3/4"
- 05. Condensate outlet 3/4"
- 06. Sprinkler valve 3/4"
- 07. Ethernet connection

	A	B	C	D	D1	E	E1	F	G	H	I	J	K	L	M	N	O	P	Q	R
in	66.69	56.97	27.13	53.31	55.98	2.68	2.68	30.91	38.94	28.94	14.96	34.25	22.64	48.27	5.24	7.09	32.68	2.56	1.38	31.69