

WASHING

FWS-65 TP2 65LB CAPACITY NORMAL SPIN WASHER



TOUCH PLUS CONTROL

- 7" touchscreen – intuitive and completely programmable
- USB Connection: software free of charge
- 37 languages, continually expanding
- Upload videos to display, use for ads, instructions, etc.

G-FORCE EXTRACTION

- 25-100 lb capacity washers: 200G
- 135 lb capacity washers: 150G

CONNECTIVITY

- FagorKonnnect, standard
- Provided at NO extra charge
- Manage your laundry operations from anywhere, 24/7
- Remote diagnosis and technical service
- Create programs, special promotions, access real-time reports, have service alerts go directly to technicians, and more

EFFICIENCY

- Low energy and water consumption
- Intelligent consumption

VERSATILITY

- Easily converts from OPL to COIN
- Electric heating < > Hot water
- Wetcleaning ready
- Extraction speed and water levels easily programmed for wetcleaning, firehouse, etc.
- Machines can be customized, made to order

ERGONOMICS & DOOR HANDLE

- Reversible doors, standard – industry exclusive
- Industry leading large doors for easy loading and unloading
- Metal door handle, commercial grade
- Door pin guide to prevent door miss locking

MAINTENANCE

- Hinged front control panel – easy and ergonomic access
- Complete technical menu
- Common parts across all models

MORE INFO

- Hard mounted washer anchoring to floor with anchoring base
- Stainless steel front and top panels
- 3 water inlets
- Drum and tub in stainless steel AISI 304
- Detergent dispenser with 4 compartments
- CB & WRAS approved product Option ETL

OPTIONS


- Anchoring base
- Auto unlock kit for door (in case of power failure) – recommended for vended laundries
- Silicon gasket
- Relay card with 6 extra dosing signals: up to 14 signals
- 5 Extra dosing pumps
- Dosing pump kit available
- Normally closed drain valve
- Double drain kit
- Sluice – Drum
- Tropicalized model: protected board
- Steam kit available
- Maritime (oil rigs) electric models available
- Coin/token kit

TECHNICAL DATA

NORMAL SPIN WASHER | FWS-65 TP2

FWS-65 TP2			
DRUM			
Load capacity	lbs	65	
Volume	cu. ft.	9.9	
Diameter	in	30.3	
Depth	in	23	
GENERAL DETAILS			
Washing speed / spinning speed	r.p.m.	48 / 682	
G Factor	-	200	
Coin laundry version	-	Yes	
Double drain	-	Opt	
Weighing System / Tilting System	-	No	
DOOR			
Height center door / Height door	in	27.5 / 15.7	
Diameter	in	18.1	
POWER			
Motor Power Consumption	hp	4.02	
CONNECTIONS		Electric Heating	Hot Water/Steam
Voltage 208-240/60/1~ + G	FLA/A	90.7/125	15.4/20
Voltage 208-240/60/3~ + G	FLA/A	50.4/70	14.5/20
Voltage 440-480/3~ + G	FLA/A	-	13.4/20
Steam inlet (Steam model)	in	3/4"	
Water inlet	in	3/4"	
Water main pressure	Kg/cm ²	2-4	
Maximum Water Consumption	Gal	43.5*	
Drain	in	3"	
Drainage capacity	Gal/min	52.8	
DIMENSIONS / PACKING DIMENSIONS			
Net width / Gross width	in	34.8 / 35.5	
Net depth / Gross depth	in	42.32 / 47	
Net height / Gross height	in	52.76 / 63	
Net weight / Gross weight	lbs	889 / 922	

* Programme No. 20, 75% load



	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	CGY	CGZ
in	34.80	42.32	52.76	15.75	18.11	5.87	21.57	41.85	48.43	41.93	49.21	44.68	2.40	2.91	3.98	16.93	20.08	31.54	25.20	10.55	32.28	30.39	48.03	22.44	47.64	23.27	23.35