



WASHING

FWS-25 TP2 25LB CAPACITY NORMAL SPIN WASHER



TOUCH PLUS CONTROL

- 7" touchscreen – intuitive and completely programmable
- USB Connection: software free of charge
- 37 languages, continually expanding
- Upload videos to display, use for ads, instructions, etc.

G-FORCE EXTRACTION

- 25-100 lb capacity washers: 200G
- 135 lb capacity washers: 150G

CONNECTIVITY

- FagorKonnnect, standard
- Provided at NO extra charge
- Manage your laundry operations from anywhere, 24/7
- Remote diagnosis and technical service
- Create programs, special promotions, access real-time reports, have service alerts go directly to technicians, and more

EFFICIENCY

- Low energy and water consumption
- Intelligent consumption

VERSATILITY

- Easily converts from OPL to COIN
- Electric heating < > Hot water
- Wetcleaning ready
- Extraction speed and water levels easily programmed for wetcleaning, firehouse, etc.
- Machines can be customized, made to order

ERGONOMICS & DOOR HANDLE

- Reversible doors, standard – industry exclusive
- Industry leading large doors for easy loading and unloading
- Metal door handle, commercial grade
- Door pin guide to prevent door miss locking

MAINTENANCE

- Hinged front control panel – easy and ergonomic access
- Complete technical menu
- Common parts across all models

MORE INFO

- Hard mounted washer anchoring to floor with anchoring base
- Stainless steel front and top panels
- 3 water inlets
- Drum and tub in stainless steel AISI 304
- Detergent dispenser with 4 compartments
- CB & WRAS approved product Option ETL

OPTIONS


- Anchoring base
- Auto unlock kit for door (in case of power failure) – recommended for vended laundries
- Silicon gasket
- Relay card with 6 extra dosing signals: up to 14 signals
- 5 Extra dosing pumps
- Dosing pump kit available
- Normally closed drain valve
- Double drain kit
- Sluice – Drum
- Tropicalized model: protected board
- Steam kit available
- Maritime (oil rigs) electric models available
- Coin/token kit

TECHNICAL DATA

NORMAL SPIN WASHER | FWS-25 TP2

FWS-25 TP2			
DRUM			
Load capacity	lbs	25	
Volume	cu. ft.	3.5	
Diameter	in	24.1	
Depth	in	12.99	
GENERAL DETAILS			
Washing speed / spinning speed	r.p.m.	53 / 759	
G Factor	-	200	
Coin laundry version	-	Yes	
Double drain	-	No	
Weighing System / Tilting System	-	No	
DOOR			
Height center door / Height door	in	22.4 /12.2	
Diameter	in	14.6	
POWER			
Motor Power Consumption	hp	1.47	
CONNECTIONS		Electric Heating	Hot Water/Steam
Voltage 208-240/60/1~ + G	FLA/A	27.5/40	5.2/15
Voltage 208-240/60/3~ + G	FLA/A	16/20	-
Voltage 440-480/3~ + G	FLA/A	-	4.7/15
Steam inlet (Steam model)	in	1/2"	
Water inlet	in	3/4"	
Water main pressure	Kg/cm ²	2-4	
Maximum Water Consumption	Gal	16.2*	
Drain	in	3"	
Drainage capacity	Gal/min	52.8	
DIMENSIONS / PACKING DIMENSIONS			
Net width / Gross width	in	28.31 / 30.5	
Net depth / Gross depth	in	29.72 / 35	
Net height / Gross height	in	45.87 / 57	
Net weight / Gross weight	lbs	437 / 520	

* Programme No. 20, 75% load



	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	CGY	CGZ
in	28.31	29.75	45.87	12.20	14.69	5.83	17.32	34.88	41.50	35.00	42.24	37.72	2.40	2.91	3.98	12.44	14.80	25.08	18.70	8.31	25.75	23.90	41.46	16.38	41.46	15.08	20.12