



accessories

Record & Stylus Cleaning Products

Record Cleaning Solution - Step 1

The Tri-Art Record Cleaning Solution is Step 1 in achieving top-level vinyl playback. Developed in the Tri-Art Lab, this gentle formula features low surface tension, so a small amount covers an entire LP side. It contains no magnetic material, helping to reduce or even eliminate static charge on your records. It works with manual record brushes, vacuum record cleaners, and ultrasonic machines to effectively remove fingerprints, LP oils and grease, and the factory protective coating from new records. Use full strength for best results, or dilute by 30–40% for very clean records, a practice many of our customers find highly effective. Available in multiple bottle sizes or by the case, in a child-resistant container; MSDS Sheet available on our website www.triartaudio.com

PID #	Size
#30443	60mL
#30444	120mL
#30445	250mL
#30607	500mL
#30608	1L
#30609	2L
#30610	3.78L
#31777	120mL Spray



[1] [2] [4]
[3]

Stylus Treatment - Step 2

Tri-Art Stylus Treatment is Step 2 and combines two functions in one product. It gently but thoroughly cleans the stylus, breaking up accumulated dust and residue to restore optimum performance. A clean stylus is essential for extracting maximum detail and preserving your record collection. At the same time, it lubricates the stylus to reduce friction and lower surface tension, improving groove tracking and helping prevent premature stylus wear or groove damage. Far from a luxury, we consider this a necessary investment in the longevity of both your vinyl and your stylus. The formula is alcohol-free and comes in a 20 mL container complete with a stylus brush.

PID #	Size
#31778	20mL

- [1] Stylus Treatment
- [2] Record Cleaner (spray)
- [3] Stylus Treatment
- [4] Record Cleaner



Gentle on your equipment



Free of magnetic materials

Vinyl Treatment - Step 3

Tri-Art Vinyl Treatment is Step 3, a final-stage vinyl preservative and lubricant designed to reduce the surface tension between stylus and groove on a properly set-up cartridge and turntable. This ultra-fine lubricant has no audible signature of its own, but the reduced friction significantly lowers record wear and groove damage. It is especially effective on new records where loud crackles are often caused by dust trapped in the grooves. Simply apply Vinyl Treatment, let it sit for 5–10 minutes, then remove with a high-quality record cleaning machine (vacuum machines deliver the best results for drying) and replay the track. If the noise is not due to permanent physical damage, the crackle will be gone. Supplied in a 120 mL recyclable spray can.

PID #	Size
#31779	120mL



Available in spray format. Bag on Valve Design- Non Aerosol



Tri-Art Manufacturing Inc.
4 Harvey Street
Kingston, ON, K7K 5B9
Canada
(613) 541-0299

PRODUCT: RECORD CLEANER

SECTION 1: IDENTIFICATION

Initial supplier identifier..... Tri-Art Manufacturing Inc.
4 Harvey Street
Kingston, ON. K7K 5B9
Canada
1-888-541-0299

Product identifier..... RECORD CLEANER

Recommended use and restrictions Record cleaner.

Other means of identification..... Not applicable.

Chemical family..... IPA solution.

Emergency telephone number and any ... Tri-Art; (613) 541-0299 (9 am to 5 pm EST).
restrictions

SECTION 2: HAZARD IDENTIFICATION



Signal Word..... DANGER.

Hazard Classification..... Flammable Liquids — Category 3. Eye Irritation — Category 2.

Hazard Description..... H226 Flammable liquid and vapour. H319 Causes serious eye irritation.

Precautionary Statements

Prevention..... P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment . P241 Use explosion-proof equipment . P242 Use non-sparking tools . P243 Take action to prevent static discharges . P264 Wash hands thoroughly after handling . P280 Wear protective gloves/protective clothing/eye protection/face protection . P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower . P370 + P378 In case of fire: Use dry sand, dry chemical, alcohol-resistant foam for extinction. P337 + P313 If eye irritation persists: Get medical advice/attention . P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing .

Response..... P403 + P235 Store in a well-ventilated place. Keep cool .

Storage..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

Disposal.....

Mixtures Statement..... This product is a mixture and has been classified in accordance with the Globally Harmonized System bridging principles. All ingredient classifications have been reviewed and been taken into consideration.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
Isopropyl alcohol	67-63-0	10-30
<<The actual concentration(s) withheld as a trade secret>>		

SECTION 4: FIRST-AID MEASURES

Routes of exposure:

Eye Contact..... Immediately flush eyes with running water for at least 5 to 10 minutes. If irritation persists, seek prompt medical attention.

Skin Contact..... Wash off with soap and plenty of water. In the unlikely event that irritation occurs, consult with your doctor.

Ingestion..... Call a physician or poison control centre immediately. Do not induce vomiting. Never give anything by mouth if victim is unconscious.

PRODUCT: RECORD CLEANER**SECTION 4: FIRST-AID MEASURES**

Inhalation.....	Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.
Most important symptoms and effects, whether acute or delayed	Isopropyl alcohol is irritating to the eyes and mildly irritating to the skin. Exposure to vapors from this product may cause irritation of the eyes and upper respiratory tract. May cause corneal injury. May cause drying and flaking of the skin.
Immediate medical attention and special . treatment needed	Treat symptomatically.

SECTION 5: FIRE-FIGHTING MEASURES

Suitable and unsuitable extinguishing media	Use water fog or fine spray, foams, carbon dioxide or dry chemical. Do not use water jet, as this may spread burning material. Use appropriate extinguishing agent for surrounding fire.
Specific hazards arising from the hazardous product	Combustible liquid and vapor. This material may be ignited by heat, sparks and direct flame. Vapours are heavier than air and collect in confined and low-lying areas. Material will float on water and can be re-ignited at the water's surface. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.
Hazardous Combustion Products.....	Oxides of carbon.
Special protective equipment and precautions for fire-fighters	Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Move containers from fire area if safe to do so. Use water to cool fire-exposed containers.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions / protective equipment	Spills on floors can create a slip hazard. Adequate precautions should be taken when walking on spilled product. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. ELIMINATE all ignition sources.
Emergency Procedures.....	Absorb. Rinse with water. Keep children and all others away from spilled material.
Methods / Materials For Containment.....	Use suitable absorbent materials such as cloth, rags, sponges, or paper towels .
Clean Up.....	Contain and wipe up the spill with absorbent material or cloth. Rinse the cloth with water and repeat the process until surface is clean and dry of spilled material .

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling.....	TREAT AS FLAMMABLE MATERIAL; KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAMES. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Keep away from extreme heat and flame. Keep containers tightly closed when not in use.
Conditions for safe storage, including any incompatibilities	Store in a cool, dry, well ventilated area. Do not freeze. Recommended storage temperature: 0 - 30°C (32 - 86°F).

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL	NIOSH
Isopropyl alcohol	200 ppm	400 ppm	400 ppm	Not established	500 ppm (STEL)	
	ON; TWA: 200 ppm STEL: 400 ppm					

Engineering Controls.....	Avoid breathing vapours or mists. Ensure that area is well ventilated. Do not use this product in an enclosed area. Remove all sources of ignition when working indoors with this product.
Personal protective equipment:	
Eye/Type.....	Take the necessary precautions to avoid liquid contact with eyes.
Gloves/Type.....	No gloves are required to handle this product.
Respiratory/type.....	Local exhaust ventilation.
Clothing/Type.....	No special protective clothing is required to use this product.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical Appearance.....	Liquid.
Color.....	Clear.
Odour.....	Mild alcohol.

PRODUCT: RECORD CLEANER**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Odour Threshold (ppm).....	No data available.
pH.....	9 - 9.5.
Melting / Freezing Point.....	< 0.
Initial Boiling Point / Boiling Range.....	>82 C.
Flash Point (deg C), Method.....	30 C.
Evaporation Rate.....	> 1.0.
Flammability (in the case of solids and ... gases)	Flammable liquid.
Upper Flammable Limit (% Vol).....	12.0.
Lower Flammable Limit (% Vol).....	2.0.
Vapour Density (Air = 1).....	> 1.
Vapour Pressure (mm Hg).....	33 hPa @ 20C (Isopropyl alcohol).
Relative Density / Specific Gravity.....	1.0.
Solubility	Completely miscible.
Coefficient of Water/Oil Distribution.....	No data.
Auto Ignition Temperature (deg C).....	> 400 C.
Decomposition Temperature.....	Not available.
Viscosity.....	1-5 poise.

SECTION 10: STABILITY AND REACTIVITY

Reactivity.....	Avoid heat and open flame. Keep away from incompatibles. Keep container tightly closed when not in use.
Chemical stability.....	Stable under the recommended storage and handling conditions prescribed.
Possibility of hazardous reactions.....	Will not occur.
Conditions to avoid, including static discharge, shock or vibration	Avoid heat, spark, open flames. Avoid static discharge.
Incompatible materials.....	Strong oxidizers. Strong acids. Aldehydes. Halogens. Halogenated organics.
Hazardous decomposition products.....	None known, refer to hazardous combustion products in Section 5.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
Isopropyl alcohol	72600 mg/m3 (Rat) 4 h	1870 mg/kg (oral, rat). 4059 mg/kg (dermal, rabbit)
ESTIMATED LD50.....	ATE: >9400 mg/kg (oral).	
Routes of Exposure:.....	Skin and eye contact are possible routes of exposure. Mists and vapours are unlikely to be generated during intended use of this product. Do not take internally or ingest this product.	
Effects Of Acute Exposure.....	Ingestion of large amounts may be harmful. If product is heated or mists are formed, inhalation may cause irritation to the nose, throat and respiratory tract. Direct skin contact may result in little or no irritation. Prolonged contact may be more irritating. Eye contact may cause mild transient irritation. May cause irritation of mouth, throat, and stomach. Swallowing may cause irritation, nausea and vomiting. If ingested, this product could be aspirated and cause lung damage.	
Effects Of Chronic Exposure.....	Repeated or prolonged skin contact can cause drying and cracking of the skin (dermatitis).	
Carcinogenicity Of Material.....	None of the ingredients in this product are classified as carcinogens by the IARC, ACGIH or NTP .	
Aggravated Medical Conditions.....	None are anticipated under normal use.	

SECTION 12: ECOLOGICAL INFORMATION

Data From Toxicity Tests..... Data from toxicity tests are not available at this time .

SECTION 13: DISPOSAL CONSIDERATIONS

Appropriate Disposal Methods..... Empty containers should be recycled in accordance with local municipal recycling practices.

PRODUCT: RECORD CLEANER**SECTION 14: TRANSPORT INFORMATION**

TDG CLASSIFICATION..... UN1219; ISOPROPANOL solution, Class 3. PG II. Limited Quantity Index: 1L.
 Environmental Hazards..... None.
 Any Special Precautions..... Refer to TDG regulations: 1.17 Limited Quantities Exemption SOR/2008-34 .

SECTION 15: REGULATORY INFORMATION

CEPA Status..... The ingredients in this product appear on the DSL .
 TSCA Inventory Status..... All ingredients are listed on the TSCA inventory.

SECTION 16: OTHER INFORMATION

Prepared By..... Trivalent Data Systems Ltd. www.trivalent.com.
 Disclaimer..... This Safety Data Sheet was prepared by Tri-Art Manufacturing and obtained from supplier information. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. Tri-Art Manufacturing Inc. disclaims all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this MSDS does not apply to use with any other product or in any other process. This Material Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of Tri-Art Manufacturing Inc.
 Date of the latest revision of the safety .. 2026-04-13
 data sheet



Tri-Art Manufacturing Inc.
4 Harvey Street
Kingston, ON, K7K 5B9
Canada
(613) 541-0299

PRODUCT: Tri-Art Audio Stylus Treatment

SECTION 1: IDENTIFICATION

Product identifier..... Tri-Art Audio Stylus Treatment
Initial supplier identifier..... Tri-Art Manufacturing Inc.
4 Harvey Street
Kingston, ON. K7K 5B9
Canada
1-888-541-0299
Emergency telephone number and any ... Contact the local poison control centre. Ontario: 1-800-268-9017 Toll-free.
restrictions
Recommended use and restrictions Intentional misuse of this product may be harmful. Cleans and lubricates turntable stylus
and reduces wear.
Chemical family..... Petroleum hydrocarbon.
Note..... Please read this safety data sheet before using this product.

SECTION 2: HAZARD IDENTIFICATION



Signal Word..... DANGER.
Hazard Classification..... H226 Flammable liquid and vapour Category 3. H304 May be fatal if swallowed and enters
airways - Aspiration Toxicity Category 1. H413 May cause long lasting harmful effects to
aquatic life.
Precautionary Statements..... P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking. P273 Avoid release to the environment. P280 Wear protective
gloves/protective clothing/eye protection/face protection. P243 Take action to prevent static
discharges. P242 Use non-sparking tools. P241 Use explosion-proof
electrical/ventilating/lighting equipment. P240 Ground and bond container and receiving
equipment. P233 Keep container tightly closed.
Response..... P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.
Rinse skin with water or shower . P331 Do NOT induce vomiting. P301 + P310 If
swallowed IMMEDIATELY CALL A POISON CONTROL CENTRE and follow instructions
provided by the centre. P303 + P361 + P353 If on skin or in hair: take off all contaminated
clothing immediately. Rinse thoroughly with water and use safety shower. P304 + P312 If
inhaled call a poison control centre or doctor; remove person to fresh air and follow
instructions from the poison control centre. P305 + P351 + P338 If in eyes rinse cautiously
with water for several minutes. Remove contact lenses, if present and easy to do. Continue
rinsing until medical help arrives. P308 + P311 If exposed or concerned; call a poison
center or doctor. P370 + P378 In case of fire - use dry chemical powder, CO2 or 6% foam.
. P370 + P378 In case of fire: Use appropriate media to extinguish.
Storage..... P403 + P235 Store in well ventilated area. Keep cool. P405 Secure storage to prevent
children from having access. .
Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.
Other hazards which do not result in In use, may form flammable/explosive vapour-air mixture. Repeated exposure may cause
classification skin dryness or cracking. If sufficient charge is allowed to accumulate, electrostatic
discharge and ignition of flammable air-vapour mixtures can occur. Even with proper
grounding and bonding, this material can still accumulate an electrostatic charge. This
material is a static accumulator.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
naphtha (petroleum), heavy alkylate	64741-65-7	95

PRODUCT: Tri-Art Audio Stylus Treatment**SECTION 4: FIRST-AID MEASURES**

General Advice.....	Not expected to be a health hazard when used under normal conditions.
Inhalation.....	No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
Skin Contact.....	Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.
Eye Contact.....	Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.
Ingestion.....	Call emergency number for your location/facility. If swallowed, do not induce vomiting; transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101F (38.3C), shortness of breath, chest congestion or continued coughing or wheezing.
Protection of First-Aiders.....	When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
Notes to Physician.....	Call a doctor or poison control center for guidance. Potential for chemical pneumonitis.
Additional Information.....	Treat symptomatically. Treat symptomatically. The main hazard from ingestion is aspiration of the liquid into the lungs.

SECTION 5: FIRE-FIGHTING MEASURES

Suitable and unsuitable extinguishing media	Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only. Do NOT use water in a jet.
Specific hazards arising from the hazardous product	Clear fire area of all non-emergency personnel. Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke); Carbon monoxide; Unidentified organic and inorganic compounds; Flammable vapours may be present even at temperatures below the flash point; The vapour is heavier than air, spreads along the ground and distant ignition is possible; Will float and can be reignited on surface water.
Hazardous Combustion Products.....	Carbon oxides; Nitrogen oxides (NOx); Polycyclic aromatic hydrocarbons; Reactive hydrocarbons; Other unidentified organic compounds.
Specific Extinguishing Methods.....	Standard procedure for chemical fires.
Special protective equipment and precautions for fire-fighters	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).
Further Information.....	Keep adjacent containers cool by spraying with water.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions / protective equipment	Observe all relevant local and international regulations. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur. Local authorities should be advised if significant spillages cannot be contained. Avoid contact with skin, eyes and clothing. Isolate hazard area and deny entry to unnecessary or unprotected personnel. Do not breathe fumes, vapour. Do not operate electrical equipment.
Environmental Precautions.....	Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Monitor area with combustible gas indicator.
Methods / Materials For Containment.....	For small liquid spills (<1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. Ventilate contaminated area thoroughly. If contamination of site occurs remediation may require specialist advice.
Clean Up.....	Do not use combustible absorbents, such as sawdust.
Additional Advice.....	For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.

PRODUCT: Tri-Art Audio Stylus Treatment**SECTION 7: HANDLING AND STORAGE**

General Precautions.....	Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material. Ensure that all local regulations regarding handling and storage facilities are followed.
Precautions for safe handling.....	Avoid inhaling vapour and/or mists. Avoid contact with skin, eyes and clothing. Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks. Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. When using do not eat or drink. The vapour is heavier than air, spreads along the ground and distant ignition is possible.
Avoidance of Contact.....	Strong oxidizing agents.
Product Transfer.....	Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements. These activities may lead to static discharge eg. spark formation. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (less than or equal to 1 m/s until fill pipe submerged to twice its diameter, then less than or equal to 7 m/s). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations. Refer to guidance under Handling section.
Conditions for safe storage, including any incompatibilities	Store in a cool, dry, well ventilated area. Keep away from incompatibles. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking in the area. Do not freeze. Always keep in containers made of the same materials as the supply container.
Other Storage Data.....	Storage Temperature: Ambient. Keep away from aerosols, flammables, oxidizing agents, corrosives and from other flammable products which are not harmful or toxic to man or the environment. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk. The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.
Packaging Material.....	Unsuitable material: Avoid prolonged contact with natural, butyl or nitrile rubbers. Do not cut, drill, grind, weld or perform similar operations on or near containers.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL	NIOSH
naphtha (petroleum), heavy alkylate	100 ppm	Not established	Not established	Not established	Not established	Not established
	NOT ESTABLISHED					

Personal protective equipment:.....	Avoid breathing vapour or mist. Avoid contact with skin, eyes and clothing. Do not eat, drink, smoke or use cosmetics while working with this product. Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities. Remove soiled clothing and wash it thoroughly before reuse.
Hand Protection.....	Where hand contact with the product may occur, the use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC, neoprene or nitrile rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for >480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time may be acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, eg. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.
Eye Protection.....	If material is handled such that it could be splashed into eyes, protective eyewear is recommended.

PRODUCT: Tri-Art Audio Stylus Treatment**SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION**

Skin and Body Protection.....	Skin protection is not required under normal conditions of use. For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure. If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standards, and provide employee skin care programmes. Wear antistatic and flame-retardant clothing, if a local risk assessment deems it so. .
Thermal Hazards.....	Not applicable.
Protective Measures.....	Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.
Hygiene Measures.....	Wash hands before eating, drinking, smoking and using the toilet. Launder contaminated clothing before re-use. Do not ingest. If swallowed, then seek immediate medical assistance.
Environmental Exposure Controls.....	Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour. Minimize release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation. Information on accidental release measures are to be found in Section 6.
Biological Occupational Exposure Limits..	No biological limit allocated.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical Appearance.....	Liquid.
Color.....	Clear.
Odour.....	HYDROCARBON ODOR.
Odour Threshold (ppm).....	No data available.
Vapour Density (Air = 1).....	> 1.
Vapour Pressure (mm Hg).....	0.07 kPa (20C /68F).
pH.....	Not applicable.
Relative Density / Specific Gravity.....	0.758.
Melting / Freezing Point.....	NOT AVAILABLE.
Solubility	negligible in water.
Initial Boiling Point / Boiling Range.....	175° to 205°C (347° to 401°F).
Evaporation Rate.....	0.1.
Flash Point (deg C), Method.....	51C.
Auto Ignition Temperature (deg C).....	347.8C / 658.0F.
Upper Flammable Limit (% Vol).....	7.0.
Lower Flammable Limit (% Vol).....	0.7.
Coefficient of Water/Oil Distribution.....	No data.
% Volatile By Weight.....	100.
Decomposition Temperature.....	Not available.
Viscosity.....	No data.

SECTION 10: STABILITY AND REACTIVITY

Reactivity.....	Avoid heat and open flame. Keep away from incompatibles. Keep container tightly closed when not in use.
Chemical stability.....	Stable under the recommended storage and handling conditions prescribed.
Possibility of hazardous reactions.....	Will not occur.
Hazardous decomposition products.....	None known, refer to hazardous combustion products in Section 5.
Incompatible materials.....	Oxidizing agents; Acids; Bases; Reducing agents.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
naphtha (petroleum), heavy alkylate	(Rat) Remarks: Low toxicity. LC50 greater than near-saturated vapour concentration.	(Rat) Remarks: Low toxicity >5000 mg/kg (Rabbit) Remarks: Low toxicity >5000 mg/kg
Routes of Exposure:.....	Skin, eyes, inhalation and ingestion.	
Skin Corrosion/Irritation.....	Causes mild skin irritation. Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis.	
Serious eye damage/eye irritation.....	Not irritating to eye.	
Respiratory or skin sensitization	Not a sensitizer. Based on available data, the classification criteria are not met.	
Germ cell mutagenicity	Genotoxicity in vivo: not mutagenic .	

PRODUCT: Tri-Art Audio Stylus Treatment**SECTION 11: TOXICOLOGICAL INFORMATION**

Carcinogenicity.....	Tumours produced in animals are not considered relevant to humans. Not a carcinogen. Based on available data, the classification criteria are not met. IARC: Group 2B: Possibly carcinogenic to humans. - naphtha (petroleum), heavy alkylate 64741-65-7 OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens. NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
Reproductive toxicity.....	Effects on fertility: Not a developmental toxicant. Based on available data, the classification criteria are not met. Does not impair fertility.
STOT - single exposure.....	Based on available data, the classification criteria are not met.
STOT - repeated exposure.....	Kidney: caused kidney effects in male rats which are not considered relevant to humans.
Aspiration toxicity.....	Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.
Note.....	Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal . Classifications by other authorities under varying regulatory frameworks may exist.

SECTION 12: ECOLOGICAL INFORMATION

Basis for assessment.....	Incomplete ecotoxicological data are available for this product. The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products.
Ecotoxicity.....	Toxicity to fish (Acute toxicity): Not toxic at limit of water solubility. Toxicity to microorganisms (Acute toxicity): LC/EC ₅₀ > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met. Toxicity to crustacean (Chronic toxicity): NOEC/NOEL > 1.0 - <= 10mg/l (based on test data). Toxicity to fish (Chronic toxicity): Data not available. Toxicity to algae/aquatic plants (Acute toxicity): Not toxic at limit of water solubility. Toxicity to crustacean (Acute toxicity): Not toxic at limit of water solubility.
Persistence and degradability	Inherently biodegradable. Oxidises rapidly by photo-chemical reactions in air..
Bioaccumulation Potential.....	Bioaccumulation: Has the potential to bioaccumulate. . Partition coefficient: n-octanol/water: Data not available. .
Mobility in soil.....	Mobility: Floats on water. If it enters soil, it will adsorb to soil particles and will not be mobile.
Other adverse effects.....	Additional ecological information: Does not have ozone depletion potential.

SECTION 13: DISPOSAL CONSIDERATIONS

Disposal Methods - Waste from residues..	Recover or recycle if possible. Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with. Do not dispose into the environment, in drains or in water courses. Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.
Disposal methods - Contaminated packaging	Drain container thoroughly. After draining, vent in a safe place away from sparks and fire. Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums. Send to drum recoverer or metal reclaimer. Comply with any local recovery or waste disposal regulations.

SECTION 14: TRANSPORT INFORMATION

TDG	
UN Number.....	1268.
Proper shipping name.....	Petroleum Distillates, N.O.S.
Class.....	3.
Packaging Group.....	III.
Labels.....	3.
Marine Pollutant.....	no.
International Regulations	
IATA-DGR	
UN/ID No.....	UN 1268.
Proper Shipping Name.....	Petroleum Distillates, n,o.s.
Class.....	3.
Packing group.....	III.
Labels.....	3.
IMDG-Code	
UN number.....	UN 1268.

PRODUCT: Tri-Art Audio Stylus Treatment**SECTION 14: TRANSPORT INFORMATION**

Proper shipping name.....	Petroleum distillates, N.O.S.
Class.....	3.
Packing Group.....	III.
Labels.....	3.
Marine pollutant.....	no.
Bulk Transport.....	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code. Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.
Special precautions for user.....	Reefer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.
Additional Information.....	This product may be transported under nitrogen blanketing. Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxygen which may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry.

SECTION 15: REGULATORY INFORMATION

Regulatory Information.....	Safety, health and environmental regulations/legislation specific for this substance or mixture: . Regulatory Information. This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR. The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.
Inventories.....	Inventories.
AIC.....	Listed.
DSL.....	Listed.
IECSC.....	Listed.
KECI.....	Listed.
PICCS.....	Listed.
EINECS.....	Listed.
TSCA.....	Listed.

SECTION 16: OTHER INFORMATION

Prepared By.....	REGULATORY AFFAIRS .
Disclaimer.....	This Safety Data Sheet was prepared by Tri-Art Manufacturing and obtained from supplier information. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. Tri-Art Manufacturing Inc. disclaims all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this MSDS does not apply to use with any other product or in any other process. This Material Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of Tri-Art Manufacturing Inc.
Date of the latest revision of the safety data sheet ..	2026-04-13



Tri-Art Manufacturing Inc.
4 Harvey Street
Kingston, ON, K7K 5B9
Canada
(613) 541-0299

PRODUCT: Tri Art Audio Vinyl Treatment

SECTION 1: IDENTIFICATION

Product identifier..... Tri Art Audio Vinyl Treatment
Initial supplier identifier..... Tri-Art Manufacturing Inc.
4 Harvey Street
Kingston, ON. K7K 5B9
Canada
1-888-541-0299
Emergency telephone number and any ... Contact the local poison control centre. Ontario: 1-800-268-9017 Toll-free.
restrictions
Recommended use and restrictions Intentional misuse of this product may be harmful. This product is intended to be used only
once per record. Repairs/restores damaged, worn records.
Chemical family..... Petroleum hydrocarbon.
Note..... Please read this safety data sheet before using this product.

SECTION 2: HAZARD IDENTIFICATION



Signal Word..... DANGER.
Hazard Classification..... H226 Flammable liquid and vapour Category 3. H304 May be fatal if swallowed and enters
airways - Aspiration Toxicity Category 1. H413 May cause long lasting harmful effects to
aquatic life.
Precautionary Statements..... P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking. P273 Avoid release to the environment. P280 Wear protective
gloves/protective clothing/eye protection/face protection. P243 Take action to prevent static
discharges. P242 Use non-sparking tools. P241 Use explosion-proof
electrical/ventilating/lighting equipment. P240 Ground and bond container and receiving
equipment. P233 Keep container tightly closed.
Response..... P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.
Rinse skin with water or shower . P331 Do NOT induce vomiting. P301 + P310 If
swallowed IMMEDIATELY CALL A POISON CONTROL CENTRE and follow instructions
provided by the centre. P303 + P361 + P353 If on skin or in hair: take off all contaminated
clothing immediately. Rinse thoroughly with water and use safety shower. P304 + P312 If
inhaled call a poison control centre or doctor; remove person to fresh air and follow
instructions from the poison control centre. P305 + P351 + P338 If in eyes rinse cautiously
with water for several minutes. Remove contact lenses, if present and easy to do. Continue
rinsing until medical help arrives. P308 + P311 If exposed or concerned; call a poison
center or doctor. P370 + P378 In case of fire - use dry chemical powder, CO2 or 6% foam.
. P370 + P378 In case of fire: Use appropriate media to extinguish.
Storage..... P403 + P235 Store in well ventilated area. Keep cool. P405 Secure storage to prevent
children from having access. .
Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.
Other hazards which do not result in In use, may form flammable/explosive vapour-air mixture. Repeated exposure may cause
classification skin dryness or cracking. If sufficient charge is allowed to accumulate, electrostatic
discharge and ignition of flammable air-vapour mixtures can occur. Even with proper
grounding and bonding, this material can still accumulate an electrostatic charge. This
material is a static accumulator.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
naphtha (petroleum), heavy alkylate	64741-65-7	95

PRODUCT: Tri Art Audio Vinyl Treatment**SECTION 4: FIRST-AID MEASURES**

General Advice.....	Not expected to be a health hazard when used under normal conditions.
Inhalation.....	No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
Skin Contact.....	Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.
Eye Contact.....	Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.
Ingestion.....	Call emergency number for your location/facility. If swallowed, do not induce vomiting; transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101F (38.3C), shortness of breath, chest congestion or continued coughing or wheezing.
Protection of First-Aiders.....	When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
Notes to Physician.....	Call a doctor or poison control center for guidance. Potential for chemical pneumonitis.
Additional Information.....	Treat symptomatically. Treat symptomatically. The main hazard from ingestion is aspiration of the liquid into the lungs.

SECTION 5: FIRE-FIGHTING MEASURES

Suitable and unsuitable extinguishing media.....	Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only. Do NOT use water in a jet.
Specific hazards arising from the hazardous product.....	Clear fire area of all non-emergency personnel. Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke); Carbon monoxide; Unidentified organic and inorganic compounds; Flammable vapours may be present even at temperatures below the flash point; The vapour is heavier than air, spreads along the ground and distant ignition is possible; Will float and can be reignited on surface water.
Hazardous Combustion Products.....	Carbon oxides; Nitrogen oxides (NOx); Polycyclic aromatic hydrocarbons; Reactive hydrocarbons; Other unidentified organic compounds.
Specific Extinguishing Methods.....	Standard procedure for chemical fires.
Special protective equipment and precautions for fire-fighters.....	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).
Further Information.....	Keep adjacent containers cool by spraying with water.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions / protective equipment.....	Observe all relevant local and international regulations. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur. Local authorities should be advised if significant spillages cannot be contained. Avoid contact with skin, eyes and clothing. Isolate hazard area and deny entry to unnecessary or unprotected personnel. Do not breathe fumes, vapour. Do not operate electrical equipment.
Environmental Precautions.....	Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Monitor area with combustible gas indicator.
Methods / Materials For Containment.....	For small liquid spills (<1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. Ventilate contaminated area thoroughly. If contamination of site occurs remediation may require specialist advice.
Clean Up.....	Do not use combustible absorbents, such as sawdust.
Additional Advice.....	For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.

PRODUCT: Tri Art Audio Vinyl Treatment**SECTION 7: HANDLING AND STORAGE**

General Precautions.....	Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material. Ensure that all local regulations regarding handling and storage facilities are followed.
Precautions for safe handling.....	Avoid inhaling vapour and/or mists. Avoid contact with skin, eyes and clothing. Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks. Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. When using do not eat or drink. The vapour is heavier than air, spreads along the ground and distant ignition is possible.
Avoidance of Contact.....	Strong oxidizing agents.
Product Transfer.....	Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements. These activities may lead to static discharge eg. spark formation. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (less than or equal to 1 m/s until fill pipe submerged to twice its diameter, then less than or equal to 7 m/s). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations. Refer to guidance under Handling section.
Conditions for safe storage, including any incompatibilities	Store in a cool, dry, well ventilated area. Keep away from incompatibles. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking in the area. Do not freeze. Always keep in containers made of the same materials as the supply container.
Other Storage Data.....	Storage Temperature: Ambient. Keep away from aerosols, flammables, oxidizing agents, corrosives and from other flammable products which are not harmful or toxic to man or the environment. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk. The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.
Packaging Material.....	Unsuitable material: Avoid prolonged contact with natural, butyl or nitrile rubbers. Do not cut, drill, grind, weld or perform similar operations on or near containers.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL	NIOSH
naphtha (petroleum), heavy alkylate	100 ppm	Not established	Not established	Not established	Not established	Not established
	NOT ESTABLISHED					

Personal protective equipment:.....	Avoid breathing vapour or mist. Avoid contact with skin, eyes and clothing. Do not eat, drink, smoke or use cosmetics while working with this product. Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities. Remove soiled clothing and wash it thoroughly before reuse.
Hand Protection.....	Where hand contact with the product may occur, the use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection. Longer term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC, neoprene or nitrile rubber gloves. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for >480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time may be acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, eg. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.
Eye Protection.....	If material is handled such that it could be splashed into eyes, protective eyewear is recommended.

PRODUCT: Tri Art Audio Vinyl Treatment**SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION**

Skin and Body Protection.....	Skin protection is not required under normal conditions of use. For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure. If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standards, and provide employee skin care programmes. Wear antistatic and flame-retardant clothing, if a local risk assessment deems it so. .
Thermal Hazards.....	Not applicable.
Protective Measures.....	Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.
Hygiene Measures.....	Wash hands before eating, drinking, smoking and using the toilet. Launder contaminated clothing before re-use. Do not ingest. If swallowed, then seek immediate medical assistance.
Environmental Exposure Controls.....	Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour. Minimize release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation. Information on accidental release measures are to be found in Section 6.
Biological Occupational Exposure Limits..	No biological limit allocated.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical Appearance.....	Liquid.
Color.....	Clear.
Odour.....	HYDROCARBON ODOR.
Odour Threshold (ppm).....	No data available.
Vapour Density (Air = 1).....	> 1.
Vapour Pressure (mm Hg).....	0.07 kPa (20C /68F).
pH.....	Not applicable.
Relative Density / Specific Gravity.....	0.758.
Melting / Freezing Point.....	NOT AVAILABLE.
Solubility	negligible in water.
Initial Boiling Point / Boiling Range.....	175° to 205°C (347° to 401°F).
Evaporation Rate.....	0.1.
Flash Point (deg C), Method.....	51C.
Auto Ignition Temperature (deg C).....	347.8C / 658.0F.
Upper Flammable Limit (% Vol).....	7.0.
Lower Flammable Limit (% Vol).....	0.7.
Coefficient of Water/Oil Distribution.....	No data.
% Volatile By Weight.....	100.
Decomposition Temperature.....	Not available.
Viscosity.....	No data.

SECTION 10: STABILITY AND REACTIVITY

Reactivity.....	Avoid heat and open flame. Keep away from incompatibles. Keep container tightly closed when not in use.
Chemical stability.....	Stable under the recommended storage and handling conditions prescribed.
Possibility of hazardous reactions.....	Will not occur.
Hazardous decomposition products.....	None known, refer to hazardous combustion products in Section 5.
Incompatible materials.....	Oxidizing agents; Acids; Bases; Reducing agents.

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
naphtha (petroleum), heavy alkylate	(Rat) Remarks: Low toxicity. LC50 greater than near-saturated vapour concentration.	(Rat) Remarks: Low toxicity >5000 mg/kg (Rabbit) Remarks: Low toxicity >5000 mg/kg
Routes of Exposure:.....	Skin, eyes, inhalation and ingestion.	
Skin Corrosion/Irritation.....	Causes mild skin irritation. Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis.	
Serious eye damage/eye irritation.....	Not irritating to eye.	
Respiratory or skin sensitization	Not a sensitizer. Based on available data, the classification criteria are not met.	
Germ cell mutagenicity	Genotoxicity in vivo: not mutagenic .	

PRODUCT: Tri Art Audio Vinyl Treatment**SECTION 11: TOXICOLOGICAL INFORMATION**

Carcinogenicity.....	Tumours produced in animals are not considered relevant to humans. Not a carcinogen. Based on available data, the classification criteria are not met. IARC: Group 2B: Possibly carcinogenic to humans. - naphtha (petroleum), heavy alkylate 64741-65-7 OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens. NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
Reproductive toxicity.....	Effects on fertility: Not a developmental toxicant. Based on available data, the classification criteria are not met. Does not impair fertility.
STOT - single exposure.....	Based on available data, the classification criteria are not met.
STOT - repeated exposure.....	Kidney: caused kidney effects in male rats which are not considered relevant to humans.
Aspiration toxicity.....	Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.
Note.....	Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal . Classifications by other authorities under varying regulatory frameworks may exist.

SECTION 12: ECOLOGICAL INFORMATION

Basis for assessment.....	Incomplete ecotoxicological data are available for this product. The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products.
Ecotoxicity.....	Toxicity to fish (Acute toxicity): Not toxic at limit of water solubility. Toxicity to microorganisms (Acute toxicity): LC/EC?IC50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met. Toxicity to crustacean (Chronic toxicity): NOEC/NOEL > 1.0 - <= 10mg/l (based on test data). Toxicity to fish (Chronic toxicity): Data not available. Toxicity to algae/aquatic plants (Acute toxicity): Not toxic at limit of water solubility. Toxicity to crustacean (Acute toxicity): Not toxic at limit of water solubility.
Persistence and degradability	Inherently biodegradable. Oxidises rapidly by photo-chemical reactions in air..
Bioaccumulation Potential.....	Bioaccumulation: Has the potential to bioaccumulate. . Partition coefficient: n-octanol/water: Data not available. .
Mobility in soil.....	Mobility: Floats on water. If it enters soil, it will adsorb to soil particles and will not be mobile.
Other adverse effects.....	Additional ecological information: Does not have ozone depletion potential.

SECTION 13: DISPOSAL CONSIDERATIONS

Disposal Methods - Waste from residues..	Recover or recycle if possible. Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with. Do not dispose into the environment, in drains or in water courses. Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.
Disposal methods - Contaminated packaging	Drain container thoroughly. After draining, vent in a safe place away from sparks and fire. Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums. Send to drum recoverer or metal reclaimer. Comply with any local recovery or waste disposal regulations.

SECTION 14: TRANSPORT INFORMATION

TDG	
UN Number.....	1268.
Proper shipping name.....	Petroleum Distillates, N.O.S.
Class.....	3.
Packaging Group.....	III.
Labels.....	3.
Marine Pollutant.....	no.
International Regulations	
IATA-DGR	
UN/ID No.....	UN 1268.
Proper Shipping Name.....	Petroleum Distillates, n,o.s.
Class.....	3.
Packing group.....	III.
Labels.....	3.
IMDG-Code	
UN number.....	UN 1268.

PRODUCT: Tri Art Audio Vinyl Treatment**SECTION 14: TRANSPORT INFORMATION**

Proper shipping name.....	Petroleum distillates, N.O.S.
Class.....	3.
Packing Group.....	III.
Labels.....	3.
Marine pollutant.....	no.
Bulk Transport.....	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code. Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.
Special precautions for user.....	Reefer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.
Additional Information.....	This product may be transported under nitrogen blanketing. Nitrogen is an odourless and invisible gas. Exposure to nitrogen enriched atmospheres displaces available oxygen which may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry.

SECTION 15: REGULATORY INFORMATION

Regulatory Information.....	Safety, health and environmental regulations/legislation specific for this substance or mixture: . Regulatory Information. This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR. The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.
Inventories.....	Inventories.
AIC.....	Listed.
DSL.....	Listed.
IECSC.....	Listed.
KECI.....	Listed.
PICCS.....	Listed.
EINECS.....	Listed.
TSCA.....	Listed.

SECTION 16: OTHER INFORMATION

Prepared By.....	REGULATORY AFFAIRS .
Disclaimer.....	This Safety Data Sheet was prepared by Tri-Art Manufacturing and obtained from supplier information. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. Tri-Art Manufacturing Inc. disclaims all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this MSDS does not apply to use with any other product or in any other process. This Material Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of Tri-Art Manufacturing Inc.
Date of the latest revision of the safety data sheet ..	2026-04-13