

Product Description

4T SCOOTER MOTOR OIL 10W-40 is a synthetic technology 4-stroke scooter engine oil formulated using selected base oils and advanced additives designed to provide reliable engine protection and smooth riding performance for modern automatic scooters.

The formulation provides effective resistance against wear, oxidation, and thermal degradation while maintaining engine cleanliness and stable lubrication performance under severe riding conditions. It is engineered to support smooth acceleration, efficient engine response, and dependable protection during stop-and-go urban operation.

4T SCOOTER MOTOR OIL 10W-40 is suitable for air-cooled and water-cooled 4-stroke automatic scooters requiring JASO MB and API SL performance level lubricants.

Specification and Requirements

- JASO MB
- API SL

Product Sizes

☐ 200 Liters ☐ 18 Liters ☐ 4 Liters ☒ 1 Liter

Main Applications



- Air-cooled and water-cooled 4-stroke automatic scooters requiring JASO MB performance level lubricants
- Modern scooter engines operating under stop-and-go urban riding conditions
- Automatic scooters requiring SAE 10W-40 viscosity grade oils for stable lubrication performance
- Scooter applications operating under elevated temperature and severe riding conditions
- Daily commuting and general scooter transportation applications

Performance Benefits

- **Reliable Wear Protection.** Provides protection for critical engine components during operation.
- **Good Thermal and Oxidation Stability.** Maintains lubricant durability under elevated operating temperatures.
- **Smooth Riding Performance.** Supports responsive acceleration and stable engine operation during daily riding conditions.
- **Engine Cleanliness Control. Helps minimize sludge and deposit formation for cleaner engine operation.**
- **Stable Lubrication Performance.** Maintains consistent lubrication characteristics under varying riding conditions.

Test Physical Characteristics

Test Parameter	Test Method	Specification
Appearance	Visual	Clear
Color, ASTM	ASTM D1500	<2.0
Density @15°C, kg/l	ASTM D7777	0.8747
Kinematic Viscosity @40°C, cSt	ASTM D445	124.4
Kinematic Viscosity @100°C, cSt	ASTM D445	14.91
Viscosity Index	ASTM D2270	123
Flash Point, COC, °C	ASTM D92	240

Health and Safety

Based on available information, this product is unlikely to produce any significant hazard on health when used for the recommended application provided in the Material Safety Data Sheet (MSDS). Guidance on Health and Safety is available on the appropriate Material Safety and Data Sheet, which can be obtained from <http://www.seaoil.com.ph>

Environment

Bring used oil to a permitted container and place. Do not throw it into the drain or soil.