

Category

Aerial

Name

Combination Aerial Pumper (CAPA)

Mobility

6x4

Mass Class

HR



(FRV model shown)

Standard Specification

Crew Capacity	Provision for Five (5) crew
Dimensions (max)	10500 L x 3820 H x 2500 W mm
Weight	25,000 kg
Cab Chassis	Scania P460 6x4 / 28,000 kg GVM / Crew Cab / 340 kW Diesel Engine / Automatic Transmission
Crew Protection	AVL
Pump	Darley PSRH1250
Pump Performance	4700 L/min @ 1000 kPa
Primer Pump	Air driven piston pump
Foam System	A Class Injected, B class ATP
Deliveries	Four (4) x 64mm BIC Female at ground Two (2) x 64mm BIC Female at platform
Collectors	Four (4) x 64mm BIC Male One (1) x 64mm BIC tank fill One (1) x 125mm Storz hard suction
Hose Reels	Two (2) electric rewind 60m x Ø25mm
Water Capacity	1700 litres
Foam Capacity	40 litre A Class foam tank 125 litres B Class foam tank
Lighting	24 volt LED Lighting
Welfare	Fridge
Aerial System	Bronto Skylift F28 ALR 28m Working Height Outreach 20m (350kg) / 22 m (130kg) Cage 350kg 3 person Dual control of aerial boom 3000 L/min remote controlled monitor Outrigger stabilisers

Primary Incident



Structure Fire



Road Crash



HAZMAT

Services

