



FOR A SAFER STATE

Category

Name

Pumper Urban Pumper Type 2

Mobility

4x2

Mass Class





Standard Specification

Crew Capacity Provision for six (6) crew
Dimensions 8600 L x 3300 H x 2500 W mm

(2900 W mm mirror to mirror)

Weight 12,700 kg

Cab Chassis Volvo FL 4x2 / 16,000 kg GVM / Crew cab /

209 kW 1050 Nm diesel engine /

automatic transmission

Crew Protection AVL, Burn over blankets

Pump Waterous CXK pump/transmission

Pump Performance 4000 L/min @ 1000 kPa Pumping Modes Stationary / Pump and Roll

Primer Pump Electric vane type

Foam System A Class Injected, B Class inducted post-

delivery

Deliveries Four (4) x 64mm BIC Female Collectors Three (3) x 64mm BIC Male

One (1) x 64mm tank fill Two (2) x 125mm Storz hard suction

Hose Reels Two (2) electric rewind 60m x Ø25mm

Water Capacity 1200 litres

Foam Capacity 60 litre A Class foam tank

200 litres B Class foam tank

Electrical 24 Volt dual battery banks Lighting Work Lights / Mast Light

Ladder 9.0m double extension / Little Giant

Welfare Fridge

Equipment Four (4) x BA sets

Primary Incident



Structure Fire



Road Crash



HAZMAT

Services





Configurations

Heavy Rescue Additional heavy vehicle rescue response

equipment

