

## Category

**Pumper**

## Name

**Urban Pumper Type 3**

## Mobility



## Mass Class



## Standard Specification

|                  |                                                                                                                      |
|------------------|----------------------------------------------------------------------------------------------------------------------|
| Crew Capacity    | Provision for six (6) crew                                                                                           |
| Dimensions       | 8450 L x 3250 H x 2490 W mm<br>(2900 W mm mirror to mirror)                                                          |
| Weight           | 12,260 kg                                                                                                            |
| Cab Chassis      | Isuzu FTS 139-260 4x4 / 13,900kg GVM /<br>Crew cab / 191 kW 761 Nm diesel engine /<br>6 speed automatic transmission |
| Crew Protection  | AVL, Radiant Heat Shields, Chassis Lagging,<br>Burn over blankets and In Cab Air                                     |
| Pump             | Waterous CLS with K type transmission                                                                                |
| Pump Performance | 1800 L/min @ 1000 kPa                                                                                                |
| Pumping Modes    | Stationary / Pump and Roll                                                                                           |
| Primer Pump      | Electric vane type                                                                                                   |
| Foam System      | A Class Injected, B Class inducted post-<br>delivery                                                                 |
| Deliveries       | Three (3) x 64mm BIC Female                                                                                          |
| Collectors       | Three (3) x 64mm BIC Male<br>One (1) x 64mm tank fill                                                                |
| Hose Reels       | Two (2) x 100mm Storz hard suction                                                                                   |
| Water Capacity   | Two (2) electric rewind 50m x Ø25mm                                                                                  |
| Foam Capacity    | 1400 litres<br>60 litre A class foam tank<br>200 litre B Class foam tank                                             |
| Electrical       | 24 volt single battery bank                                                                                          |
| Lighting         | Work lights, Mast light                                                                                              |
| Ladder           | Arion 7.65 triple extension / Little Giant                                                                           |
| Welfare          | Front opening fridge in locker                                                                                       |
| Equipment        | Four (4) x BA sets on pantograph<br>Two (2) x BA sets spare                                                          |

## Primary Incident



Structure  
Fire



Road Crash



HAZMAT

## Services



[Click Here](#) to view Walk Around Video