

Category

Name

Pumper Urban Pumper

Mobility

Mass Class

4x2

MR



Standard Specification

Crew Capacity	Provision for four (4) crew
Dimensions	8436 L x 3250 H x 2500 W mm (2900 W mm mirror to mirror)
Weight	13,500 kg
Cab Chassis	Scania P320 4x2 / 15,500 kg GVM / Crew cab / 235kW diesel engine / automatic transmission
Crew Protection	AVL
Pump	Waterous CMC20 pump/transmission / two stage impellor with volume or pressure modes
Pump Performance	4750 L/m @ 1000 kPa (flow mode)
Pumping Modes	Stationary / Pump and Roll
Primer Pump	Electric vane type
Foam System	A Class Injected, B Class inducted post-delivery
Deliveries	Five (5) x 64mm BIC Female
Collectors	Four (4) x 64mm BIC Male One (1) x 64mm tank fill Two (2) x 150mm Storz hard suction
Hose Reels	Two (2) electric rewind 60m x Ø25mm
Water Capacity	1200 litres
Foam Capacity	60 litre A Class foam tank 200 litres B Class foam tank
Electrical	24 Volt dual battery banks
Lighting	Work Lights / Mast Light
Ladder	9.0m double extension / Little Giant
Welfare	Fridge
Equipment	Four (4) x BA sets

Configurations

Heavy Rescue	Additional heavy vehicle rescue response equipment
--------------	--

Primary Incident



Structure Fire



Road Crash



HAZMAT



Heavy Rescue

Services

