

Stahlbetonrohre

EN 1916/DIN V 1201-Typ 2 **mit Fuß** DN 300-DN 2000

Nennweite	Rohraußen-Ø in mm	Wanddicke in mm			Fußbreite in mm	Spitzende Ø	Außen-Ø Glocke in mm	Fließlänge in mm	Gewicht	Muffenlänge in mm
d ₁	d _a	t ₁	t ₂	t ₃	b	dsp	dg	L	Kg/m	Iso
300	505	65	95	110	240	404	528	2500	241	80
400	615	65	100	110	320	505	630	2500	347	90
500	715	70	100	115	400	610	745	2500	443	90
600	830	85	100	130	450	726	874	2500	592	90
700	965	100	115	150	500	844	1012	2500	733	95
800	1100	115	130	170	550	962	1140	2500	1010	100
900	1240	130	145	195	600	1080	1280	2500	1250	100
1000	1375	145	160	215	650	1198	1368	2400	1470	105
1200	1560	130	150	210	735	1434	1640	2400	1712	100
1400	1790	155	155	235	1080	1670	1951	2400	2480	110
1500	1920	150	170	250	900	1670	1930	2500	2450	115
1600	1995	175	175	220	1180	1708	1995	2500	2850	125
1800	2200	200	200	250	1320	1985	2200	2500	3717	120
2000	2400	200	200	260	auf Anfrage	2166	2400	2500	4159	125

Stahlbetonrohre

EN 1916/DIN V 1201-Typ 2 **ohne Fuß** DN 300-DN 2400

Nennweite	Rohraußen-Ø in mm	Wanddicke in mm			Fußbreite in mm	Spitzende Ø	Außen-Ø Glocke in mm	Fließlänge in mm	Gewicht	Muffenlänge in mm
d ₁	d _a	t ₁	t ₂	t ₃	b	dsp	dg	L	Kg/m	Iso
300	450	75	75	75		404	528	2500	238	80
400	550	75	75	75		505	630	2500	299	90
500	650	75	75	75		610	745	2500	335	90
600	760	80	80	80		726	874	2500	460	90
700	880	90	90	90		844	1012	2500	583	95
800	1000	100	100	100		962	1140	2500	753	100
900	1120	110	110	110		1080	1280	2500	940	100
1000	1260	130	130	130		1198	1346	2400	1050	105
1100	1370	135	135	135		1316	1570	2500	1400	125
1200	1490	145	145	145		1434	1675	2500	1556	100
1400	1760	180	180	180		1618	1870	2500	1978	125
1600	2000	200	200	200		1763	1960	2500	2516	125
1800	2200	200	200	200		1985	2200	2500	2880	120
2000	1440	220	220	220		2166	2400	2500	3360	125
2400	2880	240	240	240		2607	2880	2500	4976	125

Betonrohre

Betonrohre EN 1916 / DIN V 1201-Typ 2 **mit Fuß** DN 300 - DN 1200

Nennweite	Rohraußen-Ø in mm	Wanddicke in mm			Fußbreite in mm	Spitzende Ø	Außen-Ø Glocke in mm	Fließlänge in mm	Gewicht	Muffenlänge in mm
d ₁	d _a	t ₁	t ₂	t ₃	b	dsp	dg	L	Kg/m	Iso
300	505	65	95	110	240	404	528	2500	241	80
400	615	65	100	115	320	505	630	2500	347	90
500	715	70	100	115	400	610	745	2500	443	90
600	830	85	100	130	450	726	874	2500	592	90
700	965	100	115	150	500	844	1012	2500	733	95
800	1100	115	130	170	550	962	1140	2500	1010	100
900	1240	130	145	195	600	1080	1242	2500	1250	100
1000	1375	145	160	215	650	1198	1368	2400	1470	105
1200	1650	170	190	260	730	1434	1640	2400	1712	110

Stahlbetonrohre

EN 1916 / DIN V 1201-Typ 2 mit Trockenwetterrinne
(Gerinne DN 300) DN 1200 - DN 1600

Nennweite	Rohraußen-Ø in mm	Wanddicke in mm			Fußbreite in mm	Spitzende Ø	Außen-Ø Glocke in mm	Fließlänge in mm	Gewicht	TWR
d ₁	d _a	t ₁	t ₂	t ₃	b	dsp	dg	L	Kg/m	Neigung
1200	1560	130	150	210	735	1434	1605	2400	2015	1:3
1400	1790	155	155	235	1080	1670	1951	2400	2610	1:3
1600	1995	175	175	220	1130	1708	1985	2400	3130	1:3

