



DURA-GRIP **SLIP-RESISTANT ADDITIVE**

DESCRIPTION AND BASIC USE: Proline DURA-GRIP is a micronized polymer which when added to Proline's Dura-Seal, offers slip-resistance, fine texturing and a subtle reduction of gloss. DURA-GRIP mixes easily into most decorative sealers with minimal effect on the coatings viscosity. Stir the sealer often during application to ensure even coverage.

BENEFITS: Proline DURA-GRIP is an easy addition to decorative sealers to add slip resistance to a decorative concrete project. Ideal for patios, walkways, and other high traffic areas where slip resistance is desired.

PACKAGING: DURA-GRIP is available in two convenient sizes: 8 ounces for a 5 gallon sealer, and a 2.5 ounces for a 1 gallon size sealer.

APPLICATION: If applying 2 coats of sealer, the first coat of sealer can be applied without the addition of DURA-GRIP. With the final coat, add the appropriate amount of DURA-GRIP to the sealer, mix thoroughly and apply sealer either by sprayer or roller. Sprayer should be a solvent resistant type with a "blue" tip, approximately 1/3 gpm. If rolling, use a good quality short nap roller approximately 3/8" nap is ideal. For even coverage, it is very important to keep the DURA-GRIP mixed well during the entire time of application.

CAUTION: KEEP OUT OF REACH OF CHILDREN. Before using or handling, read the Safety Data Sheet and Warranty. DO NOT TAKE INTERNALLY. Avoid contact with skin and eyes. Use only with adequate ventilation and use a respirator when exposure levels are above applicable limits.

WARRANTY: This product is not for public use and is intended for use by licensed contractors, experienced and trained in the use of these products. It is warranted to be of uniform quality with manufacturing tolerances. The manufacturer has no control over the use of this product, therefore, no warranty, expressed or implied, is or can be made either as to the affects or as results of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing material proven defective. The end user shall be responsible for determining product's suitability and assumes all risks and liability.