



Blues

LVT TECHNICAL SPECIFICATIONS

Product Dimensions:

Blues LVT Planks: 7.25" x 48" x 2.5mm, 41.094 SF/Carton

Technical Data

Following data are all supported by independent testing companies. Copies are available upon request.

TEST	RESULT
Classification / ASTM F1700	Class III, Type B (embossed)
Overall Thickness	2.5mm
Wear Layer Thickness	20 mil
Finish	UV Cured Polyurethane, Bevel
Fire Resistance / ASTM E-648	Class 1 >.45
Smoke Density / ASTM E-662	<450 – Flaming/Non Flaming
Static Load / ASTM F-970	1000 psi
Slip Resistance / ASTM D2047	R10
Impact Sound Conduction / ASTM E492	IIC 52
Chemical and Stain Resistance	Excellent
VOC Emission	Negligible

Installation

Inspect subfloor surfaces carefully to determine acceptability and appropriate installation method. All products from Siena shall be installed under proper job site conditions. Reference Siena Vinyl Flooring Installation Instructions found at sienausa.com.

Approved Adhesives

Siena recommends the use of any appropriate premium LVT adhesive.

Maintenance

Use of quality floor finishes is not required, however if desired, use of a floor finish will further protect the floor in heavy traffic areas. Chairs and table legs should be capped with metal swivel glides. Hilway Direct cleaners and floor finishes can be purchased directly from Siena. See detailed maintenance instructions at sienausa.com.

Warranty

15 year manufacture and wear warranty. Complete copy of warranty is available upon request or at sienausa.com.