



Siena Nylon Carpet Specifications : Friday Broadloom

Style Name	Friday Broadloom
Style Number	65
SPECIFICATIONS	
Construction	Tip-Sheared Loop Pattern
Yarn Content	100% Solution-Dyed Nylon
Dye Method	Solution
Machine Gauge	1/12in. (47.2col./10cm.)
Stitch Count	12 S.P.I. (39.4/10cm)
Yarn Weight Tufted	36oz./yd2
Pile Height	0.169"
Total Thickness	0.344"
Primary Backing	Woven Polypropylene
Secondary Backing	ActionBac
Recycled Content	N/A
Width	12" (3.66m)
Pattern Repeat	Random
PERFORMANCE	
Static Control	Less Than 3.5 K.V. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less Than .450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil Protection
Stain Resistance	Commercial Stain Protection
CRI Green Label Plus	Certification# GLP100203
WARRANTIES	
Limited Warranty	10 Years Limited Warranty
ADDITIONAL INFORMATION	
Backing Options	Contact Sales
Custom Colors	Contact Sales
RECOMMENDED INSTALLATION(S)	

1-888-977-4362

WWW.SIENAUSA.COM



Siena Nylon Carpet Specifications : Friday Tile

Style Name	Friday Tile
Style Number	65T
SPECIFICATIONS	
Construction	Tip-Sheared Loop Pattern
Yarn Content	100% Solution-Dyed Nylon
Dye Method	Solution
Machine Gauge	1/12in. (47.2col./10cm.)
Stitch Count	12 S.P.I. (39.4/10cm)
Yarn Weight Tufted	30oz./yd2
Pile Height	0.146"
Total Thickness	0.309"
Primary Backing	Non-Woven
Secondary Backing	Nexus Modular Backing
Recycled Content	N/A
Tile Size	24" W x 24" L (61 cm. x 61 cm.)
Pattern Repeat	N/A
PERFORMANCE	
Static Control	Less Than 3.5 K.V. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less Than .450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil Protection
Stain Resistance	Commercial Stain Protection
CRI Green Label Plus	Certification# GLP100202
WARRANTIES	
Limited Warranty	10 Years Limited Warranty
ADDITIONAL INFORMATION	
Backing Options	Contact Sales
Custom Colors	Contact Sales
RECOMMENDED INSTALLATION(S)	
	1/4 Turn, Monolithic

1-888-977-4362

WWW.SIENAUSA.COM