



Siena Nylon Carpet Specifications: ZEN GARDEN

Style Name	ZEN GARDEN
Style Number	72
SPECIFICATIONS	
Construction	Textured Cut Pile
Yarn Content	Avalar® SD Nylon
Dye Method	Solution
Machine Gauge	1/10 in. (39.4 col./10 cm.)
Stitch Count	12 S.P.I. (47.2/10 cm.)
Yarn Weight Tufted	50 oz./yd.2 (1,695 g./m.2)
Primary Backing	Woven Polypropylene
Secondary Backing	Woven Polypropylene
Recycled Content	N/A
Width	12 Feet (3.66 m.)
Pattern Repeat	N/A
Tile Size	N/A
PERFORMANCE	
Static Control	Less Than 3.5 K.V. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less Than 450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil Protection
Stain Resistance	Commercial Stain Protection
CRI Green Label Plus	Certification# GLP100203
WARRANTIES	
Nexterra®	N/A
Wear	10 Year Limited*
Stain, Static and Colorfastness	Lifetime Limited*
	*See website for full warranties
ADDITIONAL INFORMATION	
Backing Options	Contact Sales Representative
Custom Colors	Contact Sales Representative
Environmental	Proud member of the EPA's Green Power Partnership
Sustainability	N/A

1.888.977.4362

WWW.SIENAUSA.COM



Siena Nylon Carpet Specifications: ZEN GARDEN

Style Name	ZEN GARDEN TILE 72T
Style Number	
SPECIFICATIONS	
Construction	Textured Cut Pile
Yarn Content	Avalar® SD Nylon
Odor Reduction	Puralex®
Dye Method	Solution
Machine Gauge	1/10 in. (39.4 col./10 cm.)
Stitch Count	8 S.P.I. (31.5/10 cm.)
Yarn Weight Tufted	36 oz./yd.2 (1,220 g./m.2)
Primary Backing	Non-Woven
Secondary Backing	Nexus® tile backing
Recycled Content	19% Pre-consumer recycled material
Width	N/A
Pattern Repeat	N/A
Tile Size	24" W x 24" L (61 cm. x 61 cm.)
PERFORMANCE	
Static Control	Less Than 3.5 K.V. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less Than 450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil Protection
Stain Resistance	Commercial Stain Protection
CRI Green Label Plus	Certification# GLP100202
WARRANTIES	
Nexterra®	Lifetime Limited*
Wear	Lifetime Limited*
Stain, Static and Colorfastness	Lifetime Limited*
	*See website for full warranties
ADDITIONAL INFORMATION	
Backing Options	N/A
Custom Colors	Contact Sales Representative
Environmental	Proud member of the EPA's Green Power Partnership
Sustainability	Certification ANSI/NSF 140 Platinum
RECOMMENDED INSTALLATION(S)	
	1/4 Turn, Monolithic

1.888.977.4362

WWW.SIENAUSA.COM



Siena Nylon Carpet Specifications: ZEN GARDEN

Style Name	ZEN GARDEN TRIMLINE
Style Number	72L
SPECIFICATIONS	
Construction	Textured Cut Pile
Yarn Content	Avalar® SD Nylon
Dye Method	Solution
Machine Gauge	1/10 in. (39.4 col./10 cm.)
Stitch Count	8 S.P.I. (31.5/10 cm.)
Yarn Weight Tufted	36 oz./yd.2 (1,220 g./m.2)
Primary Backing	Woven Polypropylene
Secondary Backing	Woven Polypropylene
Recycled Content	N/A
Width	12 Feet (3.66 m.)
Pattern Repeat	N/A
Tile Size	N/A
PERFORMANCE	
Static Control	Less Than 3.5 K.V. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less Than 450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil Protection
Stain Resistance	Commercial Stain Protection
CRI Green Label Plus	Certification# GLP100203
WARRANTIES	
Nexterra®	N/A
Wear	10 Year Limited*
Stain, Static and Colorfastness	Lifetime Limited*
	*See website for full warranties
ADDITIONAL INFORMATION	
Backing Options	Contact Sales Representative
Custom Colors	Contact Sales Representative
Environmental	Proud member of the EPA's Green Power Partnership
Sustainability	N/A

1.888.977.4362

WWW.SIENAUSA.COM