

HT-370BE

GPON Gateway
BE6800 Dual-Band WiFi7

HEIGHTS

Main Chipset

BCM68370

Access

GPON 2.5G

Multi Service

Containerized SW

Parental

WiFi 7

2.4G 3X3

5G 4X4

Multi Link Operation (MLO)

Easy Mesh R5




Product Specifications



Wireless Features.

Wireless Standard	802.11 a/b/g/n/ac/ax/be
Wireless Signal Rates	Up to 6.8 Gbps
2.4GHz Band	3x3 11be up to 1 Gbps
5GHz Band	4x4 11be up to 5.8 Gbps
Multi link operation (MLO)	Concurrent operation of 5G+2.4G
Operating Mode	Auto by default
Wireless Communication	Enable
Wireless Security	WPA / WPA2 / WPA3
Auto channel selection	Supported
Single SSID	Supported
Steering	Band & Client steering
Security	Enabled
SSID Broadcast Control	Enabled
Transmission speed	Wireless Auto
EasyMesh Rel5	Supported



Network Features.

GPON Standard	IEEE 802.3bz 2.5G
PPPoE, DHCP, static IP connectivity	WAN connectivity on DHCP by default
NAT	Supported
MultiRangePort Forwarding Virtual server, special Application & DMZ host	Supported
DHCP Server	Supported
UPnP, DDNS	Supported
MAC Address Cloning	Supported
IGMP Snoop	Supported
QoS Traffic Control (IP)	Supported
DNS Relay	Supported
Café-style guest network	Supported



Security Features.

NAT for basic firewall support	Supported
Packet filtering firewall	Supported
Password authentication to gateway	Supported



System Features.

Configuration download / upload	Supported
Telnet / SSH	Supported
SNTP	Supported
Remote & Web management	Supported
Self-Healing	Supported
TR-069 / TR-181	Supported
Echo mode (wireless switch schedule)	Supported



Physical Features.

Interface	GPON Port , FXS, Ethernet, Power, USB3.0
Power Supply	12V 2.5A DC
Button	Reset, Power On/Off, WiFi, WPS
Dimensions	210mm x 231mm x 82mm
Operating Temperature	0° C ~ 40° C
Operating Humidity	10% ~ 90%, noncondensing
Storage Temperature	-20° C ~ 70° C
Storage Humidity	5% ~ 90%, noncondensing

Interface.

