

TREADMILL JM8

The JM8 Treadmill features a LED DOT Matrix Display. It has added comfort features such as a Fan, Quick Shift Levers, Angled Side Rails and Smooth Deck Technology to help the user workout efficiently. It also features a special inbuilt safety system that detects when the machine is running without the user and stops the machine.



One Touch Programme



Quick Shift



Angled Side Rail



Scan Here
to Access the Video

| | | | |
|-----------------------|---|------------------------|---|
| | Product features: | | Workout options: |
| Console Readout | <ul style="list-style-type: none"> Time, Distance, Calories, Heart Rate, Incline, Speed Hand held pulse handles USB Charging / CSAFE optional charging optional | Program | <ul style="list-style-type: none"> Manual, 5 Preset Programs, 3 Goal-Based Programs, 4 HRC Programs, 7 Physical Tests and Custom Programs. |
| Heart rate monitoring | | | |
| Connector | | | Comfort features: |
| Display type | <ul style="list-style-type: none"> LED Window 220V AC 15A | Accessories holder | <ul style="list-style-type: none"> Yes |
| Power Requirement | | | |
| | Performance features: | | Product dimensions: |
| Belt | <ul style="list-style-type: none"> Commercial Pre - waxed AC Inverter 0 - 16 % (16 Level) Slikdeck™ pre - waxed deck 26.4 mm 4.0 HP Continuous / 6.0 HP Peak 580 mm x 1530 mm 0.5 ~ 25 KM / H Yes Emergency stop Donut Bush Suspension 270 mm | Dimensions (L x W x H) | <ul style="list-style-type: none"> 85" x 37" x 20" 458 lbs / 208 kg 400 lbs / 182 kg |
| Controller | | Weight | |
| Incline range | | Max. user weight | |
| Deck | | | |
| Deck thickness | | | |
| Motor | | | |
| Running surface | | | |
| Speed | | | |
| Fan | | | |
| Safety control | | | |
| Shock absorption | | | |
| Step - up height | | | |

Stabilizer required: 5 KV Single Phase

Product Certifications: GS, CE.

*To be procured by the client.